



Secondary-Electron-Enhanced Plasma as an Alternative to Double/Variable-Frequency Heating in ECRIS

K. E. Stiebing, L. Schachter #, and S. Dobrescu #,

Institut für Kernphysik der Goethe-Universität, Frankfurt/Main, Germany
National Institute for Physics and Nuclear Engineering, Bucharest, Romania

(supported by [European Union 7th Framework Program FP7/2007-2013-Grant Agreement No. 262010-ENSAR](#))

Content: - Introduction
 - the MD- method
 - the IKF 14GHz ECRIS
 - the experiment
 - results



Introduction

Double Frequency Heating (DHF):

injection of two RF-waves into the ECRIS plasma chamber (typically 10GHz+14GHz, 14GHz+18GHz; 18GHz+24GHz)

Frequency Tuning (FT)-mode:

injection of two RF-waves with neighboring frequencies, with an option to sweep one of the frequencies

- two RF-transmitters required (for FT-mode one has to be broadband)
- generally works via an increase of the resonance volume of the source leading to higher electron energies (electron temperature)
- does normally not enhance confinement significantly

Metal Dielectric (MD) configuration:

thin liners with a *metal-dielectric(MD) structure* on one side are introduced in to the ECRIS plasma chamber to cover the radial walls and the extraction electrode, with *MD structure facing towards the plasma*. MD structures (e.g. Al_2O_3) are produced to possess high coefficients of secondary electron emission.

generally works via two effects:

- enhances the *plasma-electron-density* n_e by supplying cold electrons (secondary emission)
- enhances the *confinement* significantly by blocking wall currents (Simon short circuits)

The MD-method



Ar^{8+} , $P_{\text{RF}} = 1000 \text{ Watt}$

MD-effect:

- ejection of cold electrons into the plasma.
- blocking of wall currents (short circuits over the walls)
- the emission of all charge states is enhanced by 30-90% compared to the reference (all stainless steel) source.




[1] L. Sch

The MD-method

Analysis in terms of an enhancement factor:


$$\varepsilon = I_{\text{ion}} n^+_{(\text{Al-MD})} / I_{\text{ion}} n^+_{(\text{stainless steel})}$$



ε higher than 20
for Ar^{14+} !

The MD-method

comparing Al-liner with Al_2O_3 -MD-structure




→ Al-liner doesn't change the shape of CSD significantly towards higher charge states

→ Ta-MD electrode allows for extraction of higher currents of highly-charged ions as Al-MD electrode!

Ar^{14+} , $P_{RF} = 1000$ Watt

The MD-method

Using a MD-structure without significant secondary electron emission




Ta-MD-structure:


- strongly reduced output from the source. The Ta-MD liner is just an insulator without markable emission of secondary electrons and obviously
- does not change the shape of the CSD.
- Also in this scenario, the Ta-MD electrode considerably improves the extraction of ions by suppressing ion losses to the wall at the extraction hole.


Ar^{14+} , $P_{\text{RF}} = 1000 \text{ Watt}$

The MD-method




The MD-method







Results



Results



Results



Summary

METHOD	INTENSITY GAIN				REFERENCE
	Ar ¹²⁺	Ar ¹³⁺	Ar ¹⁴⁺	Ar ¹⁶⁺	
DFH/SFH	-	1.13	1.38	1.6	[1] (10+14.5) GHz / 14.5 GHz
DFH/SFH	1.74	2.02	1.07	-	[2] (10+14.5) GHz/ 14.6 GHz
FT(MD)/SFH(MD)	1.04	1.06	1.0	-	IKF this experiment
FT(MD)/standard	5	10	20	-	IKF best results for good MD performance
DFH/SFH	Xe ³⁰⁺	Xe ³¹⁺	Xe ³⁵⁺	Xe ³⁸⁺	[3] (24+18) GHz/ 24 GHz
	1.55	2.44	1.42	1.33	

[1] Z. Q. Xie, C. M. Lyneis, *Rev. Sci. Instrum.*, **66**, 8, 1995

[2] R. C. Vondrasek, R. Scott, R. C. Pardo, *Rev. Sci. Instrum.* **77**, 03A337, 2006

[3] H. W. Zhao, W. Lu, X. Z. Zhang, Y. C. Feng, J. W. Guo, Y. Cao, J. Y. Li, X. H. Guo, S. Sha, L. T. Sun and D. Z. Xie *Rev. Sci. Instrum.* **83**, 02A320 (2012)