

JOHANN WOLFGANG GOETHE

UNIVERSITÄT FRANKFURT AM MAIN



Beam Dynamics Layout of the FAIR Proton Injector

Gianluigi Clemente, Lars Groening GSI, Darmstadt, Germany

Urlich Ratzinger, R.Tiede, H.Podlech University of Frankfurt, Germany

> ICFA Workshop, Nashville TN 28th August 2008



- The FAIR Proton Injector: Overview and Requirements
- Comparison between different currents
- Alternative solutions for the beam dynamics layout
- Loss and Random Error Studies
- Conclusions & Milestones
- People



FAIR

JOHANN WOLFGANG

UNIVERSITÄT FRANKFURT AM MAIN



100 m







JOBANN WOLFGANG GOETHE UNIVERSITÄT FRANKFURT AM MAIN





- The client of the p-linac is SIS18
- Number of protons that can be put into SIS18 limited to

 $N_{SIS} = 4.305 \cdot 10^{13} \cdot \beta^2 \gamma^3$, i.e. depends on energy

Number of SIS18 turns during injection depends on phase space areas



Energy remains to be chosen



JOHANN WOLFGANG

UNIVERSITÄT FRANKFURT AM MAIN



final rate of cooled pbar depends on injector energy:





The choice of the operating frequency is a compromise between the demands of High frequency in order to optimize the RF Efficiency

$$ZT^2 \propto \sqrt{f}$$

> Low frequency to minimize the RF defocusing effect on the beam at low energy

$$\Delta p_r \propto \frac{f}{(\beta \gamma)^2}$$

and the avaibility of commercial RF feeder (klystrons, tubes, IOT's.....)

For a Multi MeV machine the best choice is to base the machine in the 300-400 MHz range which satisfies all those requirements

F = 325,244 MHz , i.e 9 x 36.13 MhZ (GSI HSI-Unilac)



The CH-DTL

JOHANN WOLFGANG GOETHE UNIVERSITÄT FRANKFURT AM MAIN



R.T and S.C. CH E< 150 AMeV 150<f<3000 MHz

H₂₁₁

Cross-Bar H-mode DTL (CH-DTL) represents the extension of well established Interdigital Linac for low-medium β velocity profile. It s geometry it's particulary suited for efficient cooling and allows the construction of high duty cicle and superconductiong linacs



H-Mode cavities in combination with the KONUS Beam Dynamics \Rightarrow Highest Shunt



- reduce number of klystrons
- reduce place requirements
- profit from 3 MW klystron development
- avoid use of magic T's
- reduce cost for rf-equipment





JOHANN WOLFGANG COETHE UNIVERSICAL Drawing FRANKFURT AM MAIN





Linac will be mounted on rails and each module is directly connected with the next one





- 14 Magnetic Triplet
- 4.9 MW of beam loading (peak), 710 W (average)
- 11 MW of total rf-power (peak), 1600 W (average)
- 41 beam diagnostic devices

RFQ-Output distributions



👂 70 mA

JOHANN WOLFGANG

UNIVERSITÄT FRANKFURT AM MAIN



| RMS ε _{norm} X-X' mm mrad | 0.362 |
|--|-------|
| RMS ϵ_{norm} Y-Y' mm mrad | 0.357 |
| RMS $\epsilon_{norm} \Delta \Phi$ - ΔW keV/ ns | 1.58 |

FAIR

Output



45 mA

JOHANN WOLFGANG

UNIVERSITÄT FRANKFURT AM MAIN



| RMS ϵ_{norm} X-X' mm mrad | 0.383 |
|--|-------|
| RMS ϵ_{norm} Y-Y' mm mrad | 0.409 |
| RMS $\epsilon_{norm} \Delta \Phi$ - ΔW keV/ ns | 2.09 |

👂 70 mA



| RMS ε _{norm} X-X' mm mrad | 0.657 |
|--|-------|
| RMS ϵ_{norm} Y-Y' mm mrad | 0.650 |
| RMS $\epsilon_{norm} \Delta \Phi$ - ΔW keV/ ns | 2.82 |

Relative RMS Increase doesn t depend on the input current!



Simplified RF and Mechanical Design

11 magnetic triplet required instead of 14

A rebuncher needed after the diagnostics section

OUTPUT for I= 45 mA







- 1. Singles errors are applied to fix the tolerances for fabrication errors and power oscillation. Single errors includes
- Transversal Quadrupole translations : ΔX , $\Delta Y \leq \pm 0.1 mm$
- **3**D Quadrupole Translations : $\Delta \phi_X$, $\Delta \phi_Y \leq \pm 1 \text{ mrad}$, $\Delta \phi_Z \leq 5 \text{ mrad}$
- Single Gap Voltage Errors : **± 1%**
- Phase Oscillations : ≤ ± 1°
- ♦ Voltage Oscillations : ≤ ± 1%
- Errors follow a gaussian distributions cut at 2 σ

Single error tolerancies doesn't depend on the current

- 2. All the sources of error are combined to evaluate the effect in terms of beam losses and RMS emittance degradation
- 3. In case 1 and 2, 1000 runs are performed with a 100 000 particles RFQ-Output Distribution

RMS Degradation 45 mA



12 CCH

JOHANN WOLFGANG

UNIVERSITÄT FRANKFURT AM MAIN



6 CCH + 3 CH-DTL





Average Transmission



Minor Losses distributed all along the machine

R

Steering correction not included

Critical point is represented by the last long CH-DTL





- The GSI Proton injector will be the first linac basedon coupled H-Mode cavities in combination with the KONUS Beam Dynamics
- Two designs are under discussions and they are comparable in terms of beam quality
- Error Studies indicated that both designs are robust enough against fabrication errors and power supplies oscillations
- Tolerances are comparable with the ones of other High Intensity linacs such as LINAC 4 or SNS
- Fabrication of the first RF Cavity (Coupled CH 3 and 4) in preparation
- Express of Interest declared by Germany, France, Russia and India
- Construction starts in 2010
- Commissioning in 2013



Partners and People



University of Frankfurt, GSI

- CH-cavity design
- RFQ design
- DTL beam dynamics
- CEA/Saclay
- Proton source & LEBT

<u>GSI Darmstadt</u> •Magnets, Power converters, Rf-sources •Proton source, Diagnostics, UHV, Civil constr., •Controls, Coordination U. Ratzinger, A. Schempp, H.Podlech R. Tiede, G. Clemente, R.Brodhage

R. Gobin et al.

G. Aberin-Wolters, R.Bär, W.Barth, P.Forck, L.Groening, R.Hollinger, C.Mühle, H.Ramakers, H.Reich, W.Vinzenz, S.Yaramyshev