


Linac4 commissioning


Transverse emittance measurement strategy

JB Lallement, A. Lombardi, P. Posocco.




Linac4 Layout

- A new 160 MeV H⁻ ion linac, injector of PS Booster.



Linac4 present status

- H- source presently under commissioning.
- RFQ delivered, RF bead-pulls performed.
- DTL, Tank1 assembled.
- First CCDTL modules delivered in October.
- PIMS modules ready from next year.
- Tunnel ready for machine installation.






Linac4 commissioning plans




- Commissioning will start next year and will be divided into 6 stages
 - Stage1: 3MeV test stand. Commissioning of the source, LEBT, RFQ and MEBT in the PS south hall.
 - Stage2: Re-commissioning of the 3MeV line in the tunnel.
 - Stage3: First DTL tank (12 MeV).
 - Stage4: DTL tank 2&3 (50 MeV).
 - Stage5: CCDTL (100 MeV).
 - Stage6: PIMS (160 MeV).

Commissioning Planning



Emittance measurement



- Low energies, up to 12 MeV
 - Low penetration depth
 - Low activation
 - Use of an emittance-meter : Slit-Grid
- High energies, 30, 50, 100 and 160 MeV
 - Three monitor method
 - Space charge to be taken into account...



The « Forward Method »

- 1st step: No space charge included, the classical 3 monitor method

$$\sigma = \begin{pmatrix} x_m^2 & x_e x'_m \\ x'_e x_m & x'_m{}^2 \end{pmatrix} = \epsilon \begin{pmatrix} \beta & -\alpha \\ -\alpha & \gamma \end{pmatrix} \quad R = \begin{pmatrix} R_{11} & R_{12} \\ R_{21} & R_{22} \end{pmatrix} \quad \sigma(L) = R * \sigma(0) * R^T$$




$$x_{monitor1}^2 = \sigma_{11}(1) = R_{11}^2(1)\epsilon\beta - 2R_{11}(1)R_{22}(1)\epsilon\alpha + R_{12}^2(1)\epsilon\gamma$$

$$x_{monitor2}^2 = \sigma_{11}(2) = R_{11}^2(2)\epsilon\beta - 2R_{11}(2)R_{22}(2)\epsilon\alpha + R_{12}^2(2)\epsilon\gamma$$

$$x_{monitor3}^2 = \sigma_{11}(3) = R_{11}^2(3)\epsilon\beta - 2R_{11}(3)R_{22}(3)\epsilon\alpha + R_{12}^2(3)\epsilon\gamma$$


The « Forward Method »

- 1st step: No space charge included, the classical 3 monitor method
@ DTL output, 50 MeV.




The « Forward Method »

- 1st step: No space charge included, the classical 3 monitor method
@ DTL output, 50 MeV.



The « Forward Method »



- 1st step: No space charge included, the classical 3 monitor method
@ DTL output, 50 MeV.



Need to include space charge forces in the calculation !!!

The « Forward Method »


- 2nd step, Including space charge, iterative process with particle tracking code.
- Generate a beam distribution file for a multiparticle tracking code, with parameters found at step 1.
- Assume a longitudinal distribution (simulations and BSM).
- Launch a series of statistical runs of the measurement line by varying the beam input transverse parameters (α , β , ϵ) at each run.
- At each run, simulated beam size at the monitor locations is compared to measured values to get a convergence criteria.



The « Forward Method »

- DTL emittance reconstruction at 50 MeV.

Twiss parameters	From beam distribution	3 monitors method No space charge	Forward method
α_x	-5.51	-3.67	-5.61
β_x (mm/mrad)	4.38	2.22	4.57
ϵ_x Norm. rms. (mm.mrad)	0.28	0.30	0.29
α_y	2.77	1.03	2.95
β_y (mm/mrad)	1.69	0.66	1.78
ϵ_y Norm. rms. (mm.mrad)	0.29	0.32	0.29



Summary

- We have developed and validated a method for the transverse emittance reconstruction in a space charge dominated regime that we will apply during the Linac4 commissioning.
- The method is based on multiparticle tracking codes and its key point is the generation of the beam distribution in the 3 phase spaces.
- Constraints are :
 - 3 monitor measurement conditions.
 - Knowledge of the longitudinal plane distribution.
 - Choice of the transverse distribution types.