

LCLS Beam Diagnostics

International Beam Instrumentation Conference 2014

Henrik Loos
September 17, 2014


- Overview
- LCLS accelerator diagnostics
- LCLS-II
- Charge and beam position
- Beam profile measurement
- Bunch length diagnostics
- Summary

LCLS and LCLS-II Beam Parameters

	LCLS		LCLS-II	Unit
	Baseline	Operation	SC	Unit
RF frequency	2856		1300	MHz
Repetition rate	120	1 – 120	10^6	Hz
Electron energy	4.3 - 13.6	2.4 – 15.4	4	GeV
Bunch charge	200 & 1000	20 – 250	10 – 100	pC
Bunch length	20	< 2 – 50	8	μm (rms)
Emittance norm.	1.2	0.13 – 0.5	0.4	μm
X-ray energy	0.83 – 8.3	0.25 – 10.5	0.2 – 5	keV
X-ray pulse energy	< 2	< 4.7	< 2.2	mJ
X-ray pulse length	230	< 5 – 500	60	fs (FWHM)


LCLS Diagnostics Development

- Machine tuning optimization
 - Fast wire scanner
- High brightness beam issues
 - YAG screen (PSI)
- New capabilities
 - SXRSS, overlap diagnostics
- Extended machine parameters
 - Low charge mode
 - Mid IR spectrometer
 - XTCAV
- LCLS-II
 - BPM μ TCA receiver
 - RF-BPM (PAL)



LCLS-II Diagnostic Challenges


- Single bunch properties like LCLS-I
- High beam power
 - Put (almost) nothing into the full rate beam
 - Low rate (diagnostic) or variable rate (post-spreader) lines for most invasive diagnostics
- High beam rate
 - Fast DAQ needed, FPGA processing, low latency networks for feedback, MPS, etc.
 - Single shot detector signals
- Low charge mode
 - BPM & R-BLM sensitivity




Courtesy J. Frisch

Charge Measurement Upgrade

- Existing toroid electronics issues
 - only local calibration
 - up to 15% read-back variation
 - Up to 4% noise at 150 pC from up to 500' cable run (BPMs give 0.05%)
- New electronics and DAQ
 - Add remote calibrator to in-tunnel amp
 - Use differential cable
 - Gated charge amplifier CAEN QDCV965A already used for PMTs
- Get ~1% agreement for absolute charge between two toroids
- Noise of 0.2% to 0.5%
- LCLS-II requires high dynamic range average current measurement, use commercial solution (Bergoz Turbo-ICT)





-
- The diagram illustrates the EPICS Channel Access Network architecture. A BPM (Beam Position Monitor) is connected to a MicroTCA Crate. The MicroTCA Crate contains four main components: the RTM (Readout Trigger Module) Analog Front End and Calibrator, the Digitizer, the IOC (CPU) running RT Linux, and the EVR (Timing). The RTM is configured with $F_c = 300 \text{ MHz}$ and $BW = 15 \text{ MHz}$. The Digitizer has a resolution of 16 bit and a sampling rate of 109 Ms/s. The IOC (CPU) is connected to the EPICS Channel Access Network. The EVR (Timing) is connected to a Timing System. The entire system is connected to the EPICS Channel Access Network via a green line.




7

LCLS Test Installation


- Implemented for 4 strip-line BPMs in L3 linac
- Operational for almost 2 years without issues
- Achieve same resolution as from existing electronics




X-Band RF Cavity BPM



SLAC Receiver Schematic





- PAL-SLAC collaboration
- 11.424 GHz (4x S-band) for flexible bunch pattern
- New receiver with coax input and μ TCA
- Test BPM next to ANL undulator RF-BPM
- Preliminary results already meet $<1 \mu\text{m}$ LCLS-II requirement
- Noise issue with power supply resolved, awaiting beam test



- Most critical performance at 10 pC low charge limit
- Strip-line BPMs (30 μm) for most of beam transport
- RF cavity BPMs in special locations, X, S, or L band
 - Energy measurement
 - Orbit for fast feedback
 - Wire scanner jitter correction
 - Undulators
- Cold button BPMs inside cryo-modules (100 μm)



Fast Wire Scanner

- COTR makes WS critical for LCLS beam tuning
- LCLS uses existing SLC design
 - Stepper motor driven, mm/s speed
 - Vibrations from wire card support on single side and stepper motor
 - 45° actuator with 3 wires for x, y, u plane
- Fast wire scanner development
 - Linear motor, up to m/s speed possible
 - 2 bellows to cancel vacuum forces
 - Also 45° scan orientation, 2" stroke for 3 wires
 - Encoder with sub- μ m resolution





FWS Motion Profile

- Motion profile to minimize scan time
- Beam synchronous data acquisition of encoder position and beam loss signal
- Makes motion stability not critical
- SLC-style 4 location emittance measurement for x, y, and coupling takes 8 min
- Expect < 30 sec with FWS
- Upgrade project started for LCLS





FWS Magnetic Shielding

- First prototype installed upstream of undulators
- Observed significant drop in FEL during scan
- Related to $\sim 20 \mu\text{Tm}$ magnetic field from linear motor



- μ -metal shielding was added
- Now reduced to $\sim 1 \mu\text{Tm}$
- Tolerance limit for LCLS & LCLS-II

- MW beam power
- Carbon wire for least beam loss
- Scan simulation with typical beam parameters of wire heating
- Stays below safe fluence studies established for SLC





- Speed of 400 mm/s already demonstrated with FWS
- Higher speed requires longer stage
- May add thick wire for beam halo measurement

Injector OTR Measurements



SLAC

- Straight beam path, no COTR affect on beam size
 - OTR and wire scanner emittance agree
 - Laser heater chicane
 - introduces small R56, see 2x COTR enhancement, emittance 25% too small
 - Energy modulation from laser interaction in undulator
- Enhancement reduced to 20%
- See laser 2. harmonic
 - Emittance still underestimated
- Even small enhancements of COTR can affect emittance measurements



SwissFEL Profile Monitor




- PSI development
- Installed at SLAC for GeV beam test at factor 10^5 COTR location
- YAG viewing geometry
 - Smallest spot size
 - COTR reflected away from CCD
 - Tilted focal plane needs tilted CCD




Talk R. Ischebeck, TUCYB3

Commissioning Results


- Saturation of YAG tested
 - None at 20 pC, indication at 180 pC
- Test for coherent enhancement
 - Scan RF phase to change bunch length
 - COTR enhancement reduced from 10^5 to small factor at full compression or 10's of percent in normal setup



SXRSS Beam Overlap Diagnostics






- Soft X-Ray Self Seeding (500 – 1000 eV)
- Both beams diverted by chicanes
- Need diagnostics to measure both
- Combine wire scanner and YAG screen
- Wire 40 μm carbon, YAG 20 μm thick
- View both with CCD camera
- ~10 μm position measurement needed





Overlap Diagnostics Performance

- Move supporting girder to scan wire and find e-beam position
- Move x-ray mirror to steer x-rays onto YAG, find position
- Use mirror response matrix to overlap beam, get seeding
- CR effects are serious issue




Mid-IR Spectrometer

- C*R based bunch length measurement of LCLS um and sub-um beams needs 1-20 μm
- Single shot preferred
- KRS-5 prism based spectrometer developed
- Images OTR from foil onto 128 element pyroelectric line array
- Transfer function determined by fitting spectra at different bunch lengths to simulated bunch spectra



MIR Spectrometer Results

- Form-factor extrapolation for $\lambda > 20 \mu\text{m}$ necessary
- Bunches as short as $0.7 \mu\text{m}$ rms at 20 pC measured



T. Maxwell et al., PRL 111, (2013) 184801



- Non-invasive version possible using CER from DL2 bends

LCLS-II Bunch Length Monitors

- Relative BLMs similar to LCLS-I detecting edge radiation
- R-BLMs at full beam rate for feedback system
- Average THz radiation power at few W level becomes issue
 - Required attenuation leaves insufficient single shot energy
 - Cooled pyroelectric detectors being investigated
- High dynamic range from wide charge and length range
 - Use of Schottky diodes at few 100 GHz with much higher sensitivity
- Fast detector response for MHz rate

X-Band Deflecting Cavity



- Existing S-band deflecting structure about 5 μm resolution
- X-band provide $\sim 10\times$ better
 - 4x higher frequency
 - 2.5x higher gradient
- Installation post-undulator in main dump beam line
 - Non-invasive for FEL users
- Direct observation of longitudinal phase space on dump YAG



C. Behrens et al., Nat. Commun. 5 (2014) 3762

XTCMV Bunch Length Measurement




- Simple calibration with phase sweep
- Bunch length with fit to off and $\pm 90^\circ$
- Achieved resolution
 - 1 fs (4 GeV)
 - 4 fs (14 GeV)
- Doubling plan using SLED



- Checked R-BLM calibration
- 5% average deviation to XTCMV
- R-BLM not sensitive below 2 μm

XTCAV as FEL and X-Ray Diagnostics

- X-ray pulse reconstruction
 - Compare FEL off and on
 - Measure time resolved energy loss
 - Energy spread increase also used



- Longitudinal bunch manipulations
 - Slotted foil emittance spoiler
 - Double bunch setup

- Diagnostics was sufficient for first LCLS operation
- New developments driven by enhancements in beam parameter range and capability, and also operational needs
- LCLS-II diagnostics benefits greatly from existing projects, but still many challenges remain

Thank you for your attention!

Special thanks to the diagnostics teams for

Toroids: D. Brown, S. Condamoor, R. Larsen

PAL RF-BPM: S. Babel, C. Kim, S. Hoobler, P. Krejcik, A.
Young, C. Xu

Fast Wire Scanner: S. Anderson, M. Campell, A. Cedillos,
M. D'Ewart, P. Krejcik, R. Iverson, Z. Oven