





The Injector Cryomodule for e-Linac at TRIUMF


R. Laxdal, C. Beard, S. Koscielniak, A. Koveshnikov, A. Mitra, T. Ries, I. Sekachev, V. Zvyagintsev (TRIUMF, Vancouver),
M. Mondal, V. Naik (DAE/VECC, Kolkata)

PAC11, WEOCS6, March 30, 2011




E-Linac Cryomodules

- TRIUMF is building an electron linac (50MeV/10mA) as a second driver for radioactive ion beam production for the ISAC facility
 - see **Shane Koscielniak talk Thursday afternoon for overview**
- E-Linac requires one nine-cell in the injector section and four nine-cell cavities in the accelerator section – choose 1+2+2 cavities/cryomodule
 - **Injector Cryomodule (ICM) to be used as a working prototype for Accelerator Cryomodule (ACM)**
 - **Two ICM's will be built and tested with beam - one for TRIUMF and one for VECC (Kolkata)**
 - **Two cavity ACM fits staging scenarios and is conveniently sized**
- 1.3GHz Cavities require operation at 2K, two cw 50kW power couplers per cavity required to supply beam loading of 100kW/cavity





VECC/TRIUMF Collaboration





VECC/TRIUMF Collaboration

ISAC-II Vault

12m

- Will use an existing lab space in ISAC-II for a beam test with 30kW rf source
- will test the front end of e-Linac by 2012
- E-Gun
 - 100kV gun available for initial LEBT commissioning
 - 300kV gun in design (TUP017)
- LEBT design finalized – in procurement phase
- ICM design in progress

2K pumps


30kW IOT System

Equipment Racks


Power coupler test station

Cry

Injector Test Layout - 2012




Injector Test Layout - 2012




Cryomodule Concepts (end load)


- Typically elliptical cavities housed in pipe like vacuum chambers with cold-mass loaded from one end
- 2K production from custom cold box or local JT expansion valve box



XFEL/ILC Style



Daresbury HI Module (Stanford)



Cornell (after Tesla)

Low beta cryomodules – top load

- Low beta cryomodules tend to utilize the top loading box concept


- Large transverse cavity dimensions
- Cavities loaded on strongback
- 4K helium reservoir/phase separator on board
- Common or separated vacuum solutions available



ISAC-II top-loading box cryomodule



Cryomodule design philosophy

- ICM and ACM's will be installed in stages- ICM will be tested in ISAC-II (4K plant) then delivered to e-Hall
 - Convenient to make each cryomodule self sufficient as far as 2K production – each equipped with heat exchanger and JT valve
- Decide to take advantage of experience with ISAC-II as far as practical to reduce design time and take advantage of existing infrastructure




ISAC-II vs e-Linac Cryogenics

- E-Linac cryogenic system borrows significantly from ISAC-II
 - Cold box delivers 4K liquid to a central supply dewar
 - 4K liquid at $\sim 1.3\text{Bar}$ is delivered to a trunk line and distributed in parallel to each of the cryomodules
 - Phase separator in each cryomodule collects 4K liquid with cold vapour returned to the cold box
- Expansion to 2K within each module
 - LHe is expanded in JT valve to produce 2K liquid
 - Sub-atmospheric pumps maintain 30mBar operating pressure



e-Linac cryogenic system




ISAC-II vs e-Linac cryomodule

•E-Linac cryomodule borrows significantly from ISAC-II

- Top loading box concept
- Strongback mounted from struts
- LN2 thermal shield
- 4K phase separator on board


•Key differences

- Cold mass operates at 2K
- Elliptical cavities vs quarter wave cavities
- MLI ok – separated vacuum




ACM


e-Linac Cryomodule features




- Top loading box concept
- Cryogenic insert with 4K phase separator JT valve and heat exchanger on board to produce 2K liquid; insert is removable with cryomodule in situ
- Cold mass supported by strong-back
- LN2 cooled thermal shield; 4K circuit for intercepts
- Warm and cold mu-metal
- Pair of alignment pick-ups upstream and downstream of each cavity

Cryogenic Couplings









Vacuum chamber

- Stainless steel ribbed enclosure
- window openings for power coupler installation
- End ports for beam pipe, WPM ports and warm isolation valve
- Top opening for cryo insert; side window for cryo-connections
- Top ports for vacuum pumps, WPM cables, tuner actuator, rf pick-ups, diagnostics (temp sensors, heaters, level probes)




Cavity parameters



- Baseline cavity is the 1.3GHz Tesla 9-cell bulk niobium cavity
- Two power couplers (50kW cw each) limit $P_{rf} \leq 100\text{kW}$ per cavity; means $\Delta E \leq 10\text{MeV}$ for $I=10\text{mA}$ – corresponds to $E_a=10\text{MV/m}$ design specification – 10W at $Q_0=1e10$
- End cells are modified to accommodate the large power couplers and mitigate higher order modes driven by high beam current



Strongback





- Cavity sub-assemblies are formed into a hermetically sealed unit (cavity string) bounded by isolation valves and containing cold power coupler, two phase pipe and WPM supports
- The cavity string is then outfitted with magnetic shielding and tuners and then mounted to the strong back for alignment




Alignment

- A pair of alignment brackets are placed upstream and downstream of each cavity fixed to the beam tube and indexed to the beam center
- The brackets can host optical or WPM targets
- Variable mounting supports from cavity to strongback are used to align the targets




Power coupler gymbal and mock-up

- Need to maintain support for power coupler while allowing it to move under cooldown and maintain low stress on window
- Design gimbaled support system
- Making a mock-up tank-flange and power coupler cavity flange to test range of motion of coupler
- Useful for working out installation of warm coupler end to installed cold part



Gimbal support for power coupler




Couplers installed

Cavity tuner and end flange


- End flange

- Utilize angled end flange and warm isolation valve
- ie ATLAS Energy upgrade cryomodule




- Cavity tuner

- Utilize JLab scissor tuner with long actuator and warm motor on top of cryomodule




Cryo-insert design

- Design enables prototyping and testing of cryo-insert in existing test cryostat (141MHz cavity cryostat)




Cryogenic-insert Design

4K/2K cryo-insert



Accelerating Cryomodule



141MHz Test Cryostat



- E-Linac cryomodule concept
 - ISAC-II design features incorporated where possible to save engineering time and profit from available infrastructure
 - Cryomodule – top loading box with 4K to 2K production on board
 - 4K cold box delivers 4K liquid at 1.3 Bar in parallel to each cryomodule phase separator
- Status
 - Cavity being prototyped in copper at PAVAC
 - Soon to start fabrication in niobium
 - 4K/2K insert in procurement phase
 - ICM detailed design on-going
 - Plan for a beam test in 2012

Thank You!

Merci!