NAME OF MACHINE Uppsala Synchrocyclot INSTITUTION The Gustaf Werner Ins	ron DATE August 1978
INSTITUTION The Gustaf Werner Ins	titute, University of Uppsala
INSTITUTION The Gustaf Werner Ins ADDRESS BOX 531, S-751 21 Upp	sala, Sweden
INCHARGE Prof. Helge Tyrén	REPORTED by Stig Holm
HISTORY AND STATUS	MAGNET
DESIGN, date 1946 MODEL tests 1947	POLE FACE diametercm; R extractioncm
ENG. DESIGN, date 1946-1951 CONSTRUCTION, date 1947 - 1951	GAP, min cm; Field kG) 6
CONSTRUCTION, date 1947 - 1951	GAP, min cm; Field kG at X 10 ⁶
FIRST BEAM date (or goal) int. Dec51 ext56	AVERAGE FIELD at R ext kg
MAJOR ALTERATIONS Complete reconstruction	CURRENT STABILITYparts/10 ⁶ ; B _{max} /〈B〉
1977-	NUMBER OF SECTORS ; SPIRAL, maxdeg
OPERATION, hr/wk; On Target hr/wk	POLE FACE COIL PAIRS: AVF/sec;
TIME DIST., in house%, outside%	Harmonic correction
USERS' SCHEDULING CYCLEweeks	Rad grad/sec or Circ coils
COST, ACCELERATOR	WEIGHT: Fetons; Coilstons
COST, FACILITY, total FUNDED BY Gustaf Werner	CONDUCTOR, Material and type
FUNDED BY Gustaf Werner	STORED ENERGYMJ
	COOLING SYSTEM
ACCELERATOR STAFF, OPERATION and DEVELOPMENT	POWER: Main coilsmax, kW
SCIENTISTS 15 ENGINEERS 7	Trimming coilsmax, kW
scientists 15 engineers 7 technicians 4 crafts 7	YOKE/POLE AREA%
GRAD STUDENTS involved during year	SECTOR ANGLE (Sep Sec)deg
OPERATED BY Res staff or Operators	SECTOR ANGLE (Sep Sec) deg ION ENERGY (Bending limit) $E/A = q^2/A^2$ MeV
BUDGET, op & dev\$ 500.000	(Focusing limit) E/A =q/A MeV
FUNDED BY Govt. and Govt. Research Counsi	ACCELERATION SYSTEM
DESEA DOUGTABE and included chaus	DEES, numberangledeg
RESEARCH STAFF, not included above	BEAM APERTUREcm; DC BIASkV
USERS, in house outside	TUNED by, coarse fine
	TUNED by, coarse fine
RES. BUDGET, in house \$ 400.000 FUNDED BY GOVT. and GOVT.Res.Couns	Orb F to mHz; GAIN, maxkV/turn
FUNDED BY dove. and dove. Nes. cours	HARMONICS, RF/Orb F, used
	DEE-Gnd, max kV, min gap cm
FACILITIES FOR RESEARCH	STABILITY, (pk-pk noise)/(pk RF volt)
SHIELDED AREA, fixed m ²	RF PHASE stable to ±deg
movablem ²	RF POWER input, maxkW
TARGET STATIONS in rooms	RF PROTECT circuit, speed µsec
STATIONS served at same time, max	Type
MAG SPECTROGRAPH, type	FREQUENCY MODULATION, rate/sec
COMPUTER, model	MODULATOR, type
OTHER FACILITIES	BEAM PULSE, width
	VACUUM SYSTEM
	PUMPS, No., Type, Size
	OPERATING PRESSURE
REFERENCES/NOTES	PUMPDOWN TIMEhrs
	ION SOURCES/INJECTION SYSTEM
	EXTRACTION SYSTEM
	EXTRACTION OTOTEM
	CONTROL SYSTEM

ENTRY NO. FM-7 (cont.)

CHARACTERISTIC BEAMS			BEAM PROPERTIES					
		Goal	Achieved	Mea	sured	Condi	tions	
	Particle	(Me∨)	(Me∨)	Pulse WidthF	RF deg	μA of	MeV	_
ENERGY P d 3He	15-200		Phase Exc, maxF	RF deg	μA of	MeV		
	25-100		Extract Eff9	%	μA of	MeV		
	75-280		Res, ΔE/E	%	μA of	MeV		
	4He	25-200		Emittance				
CURRENT Internal		(μA) ≤ 10 ≤ 50	(μΑ)	(mm-mrad)	axial }	μA of	MeV	
³ _{He,⁴He}		<u>₹30</u> <u>₹25</u>		OPERATING PROGRAMS, time dist				
External p s 3 d He, 4 He	€ 8		Basic Nuclear Physics	50			%	
	40		Solid State Physics				%	
	20		Bio-Medical Applicati	ons 30			%	
			Isotope Production	20			%	
Secondary	(part/s)	(part/s)	Development				%	
								%
								%

PLAN VIEW OF FACILITY, NOTEWORTHY FEATURES, OPERATION SUMMARY, ADDITIONAL REFERENCES

The cyclotron is under reconstruction to a sectorfocussed machine. High energy protons and ³He particles will be accelerated with frequency modulation while isochronous operation will be possible for lower energies and for other particles. A new building for an enlarged experimental area is being projected.