

ENTRY No. 71 Cyclotron (AIC-144)
 NAME OF MACHINE Automatic Isochronous V. DATE
 INSTITUTION Institute of Nuclear Physics
 ADDRESS Krakow, Poland, Radzikowskiego 152
 TEL 37 02 22 TELE
 IN CHARGE J. Schwabe REPORTED BY J. Schwabe

HISTORY AND STATUS

DESIGN, date 1976-78 Model tests 1977-79
 ENG DESIGN, date 1979
 CONSTRUCTION, date 1980-85
 FIRST BEAM, date (or goal) 10.04.87
 MAJOR ALTERATIONS

COST, ACCELERATOR

COST, FACILITY, total
 FUNDED BY

ACCELERATOR STAFF, OPERATION AND DEVELOPMENT

SCIENTISTS 7 ENGINEERS 12
 TECHNICIANS 7 CRAFTS

GRAD STUDENTS involved during year

OPERATED BY Research staff or Operators

OPERATION hr/wk, On target hr/wk

TIME DISTR. in house %, Outside %

BUDGET, op & dev

FUNDED BY

RESEARCH STAFF, not included above

USERS, in house outside

GRAD STUDENTS involved during year

RESEARCH BUDGET, in house

FUNDED BY

MAGNET

POLE FACE, diameter (compact) 144 cm, R extraction 63,5 cm

R injection 0,5-1 cm

GAP, min 11,2 cm, Field 20,5 kG } at 710(A)x672(W)

max 22 cm, Field 14,5 kG } Ampere turns

AVERAGE FIELD at R ext 17,5 kG

B number 1,17

NUMBER OF SECTORS { compact 4 } Spiral, max 5,4 deg

SECTOR ANGLE (SSC) { separated 4,5 } deg

TRIMMING COILS circular 15

valley 8

CONDUCTOR, material and type Cu

STORED ENERGY (cryogenic) MJ

POWER: main coils 240 max, kW; current stability 4×10^{-5}

trimming coils 120 max, kW; current stability 10^{-5}

WEIGHT: Fe 150 tons; coils 2 x 7,55 tons

COOLING system

ION ENERGY (bending limit) E/A = 60 (56). q^2/a^2 MeV/amu

(focusing limit) E/A = 60 (56). q^2/a^2 MeV/amu

ACCELERATION SYSTEM

DEES, number 1; angle 180 deg

BEAM APERTURE 16 cm; DC Bias kV

TUNED by, coarse panels fine trimmers, capacit.

RF 8 to 26 MHz, stable $\pm 10^{-7}$

Orb F 8 to 26 MHz

HARMONICS, RF/Orb F, used 1

DEE - Gnd, max 50 kV, min gap 2,79 cm

STABILITY, (pk-pk noise)/(pk RF volt) 10^{-4}

ENERGY GAIN, max 100 kV/turn

RF PHASE, stable to $\pm 15 \pm 4,5$ deg

RF POWER input, max 150 kW

FREQUENCY MODULATION, rate 10 ± 1000 /s

modulator, type

beam pulse, width structure; 15,6-4,8 ns; pulse: 1,25 μ s.

VACUUM SYSTEM

OPERATING PRESSURE $6 \cdot 10^{-6}$ Torr or mbar

PUMPS, No, Type, Size 2 diffusion oil pumps 4800 L/S

ION SOURCES

Penning Internal

INJECTION SYSTEM

Internal or external with electrostatic inflector

EXTRACTION SYSTEM

Electrostatic deflector, 3 sector

FACILITIES FOR RESEARCH

SHIELDED AREA, fixed m²; movable m²

TARGET STATIONS in rooms

STATIONS served at same time, max

MAG SPECTROGRAPH, type

COMPUTER model

OTHER FACILITIES

CHARACTERISTIC BEAMS

PARTICLE	ENERGY (MeV)		CURRENT (μ A)	
	Goal	Achieved	Internal	External
p	60			
d	30	25	> 400	
α	60	52	50	

SECONDARY (part/s)

BEAM PROPERTIES

MEASURED CONDITIONS

PULSE WIDTH 35 RF deg μ A of 25 MeV d ions

PHASE EXC, max RF deg μ A of MeV ions

EXTRACT eff % μ A of MeV ions

RESOL $\Delta E/E$ % μ A of MeV ions

EMITTANCE

(π mm. mrad) { 12 axial } μ A of MeV R d ions

{ 15 rad }

OPERATING PROGRAMS, time distribution

BASIC NUCLEAR PHYSICS .. SOLID STATES PHYSICS ..

BIOMEDICAL APPLICAT. ISOTOPE PRODUCTIONS ..

REFERENCES/NOTES

- 1) International seminar on isochronous Cyclotron technique
 Poland Krakow J.N.PH. 13 \pm 18 Nov. 1978
 report JFJ No.1069/PL

PLAN VIEW OF FACILITY, NOTEWORTHY FEATURES, COMMENTS

