

# Commissioning of the Rare-RI Ring at the RIKEN RI Beam Factory




**Yoshitaka Yamaguchi** on behalf of rare-RI ring collaboration


COOL'15 workshop : October 2, 2015

# Location and Feature

**RI Beam Factory**



# Location and Feature




**A storage ring dedicated to mass measurements of exotic nuclei based on Isochronous Mass Spectrometry (IMS)**

- Measurement time is as short as 1 ms
- Expected mass resolution is in the order of ppm
- Self-trigger mechanism with a fast-kicker system


# Self-trigger mechanism

- Trigger signal to excite the kicker is generated by injecting RI itself at F3.
- Kicker magnetic field needs to be excited before the RI arrives.



# Self-trigger mechanism

- Trigger signal to excite the kicker is generated by injecting RI itself at F3.
- Kicker magnetic field needs to be excited before the RI arrives.



## Relative mass measurements with references in IMS



$$\frac{m_1}{q} \gamma_1 \beta_1 = \frac{m_0}{q} \gamma_0 \beta_0$$

$$\beta_1 T_1 = \beta_0 T_0$$




$$\frac{m_1}{q} = \left( \frac{m_0}{q} \right) \frac{1}{T_0} T_1 \sqrt{\frac{1 - \beta_1^2}{1 - ((T_1/T_0) \beta_1)^2}} = \left( \frac{m_0}{q} \right) \frac{1}{T_0} T_{1\text{corr}}$$

# Simulation for $^{78}\text{Ni}$




$^{82}\text{As}$	$^{83}\text{As}$	$^{84}\text{As}$	$^{85}\text{As}$
$^{81}\text{Ge}$	$^{82}\text{Ge}$	$^{83}\text{Ge}$	$^{84}\text{Ge}$
$^{80}\text{Ga}$	$^{81}\text{Ga}$	$^{82}\text{Ga}$	$^{83}\text{Ga}$
$^{79}\text{Zn}$	$^{80}\text{Zn}$	$^{81}\text{Zn}$	$^{82}\text{Zn}$
$^{78}\text{Cu}$	$^{79}\text{Cu}$	$^{80}\text{Cu}$	$^{81}\text{Cu}$
$^{77}\text{Ni}$	$^{78}\text{Ni}$	$^{79}\text{Ni}$	$^{80}\text{Ni}$
$^{76}\text{Co}$	$^{77}\text{Co}$	$^{78}\text{Co}$	$^{79}\text{Co}$



# Simulation for $^{78}\text{Ni}$



# Simulation for $^{78}\text{Ni}$






## Expected mass resolution

$$\frac{\delta(m_1/q)}{m_1/q} = \frac{\delta(m_0/q)}{m_0/q} + \frac{\delta(T_1/T_0)}{T_1/T_0} + k \frac{\delta\beta_1}{\beta_1} \quad k = -\frac{\beta_1^2}{1-\beta_1^2} + \left(\frac{T_1}{T_0}\right)^2 \frac{\beta_1^2}{1-(T_1/T_0)^2\beta_1^2}$$

ppm order  $< 10^{-6}$      $\sim 10^{-6}$      $\beta_1 \sim 10^{-4}$  ( $k \sim 10^{-2}$ )

# Simulation for $^{78}\text{Ni}$




## Expected mass resolution

$$\frac{\delta(m_1/q)}{m_1/q} = \frac{\delta(m_0/q)}{m_0/q} + \frac{\delta(T_1/T_0)}{T_1/T_0} + k \frac{\delta\beta_1}{\beta_1} \quad k = -\frac{\beta_1^2}{1-\beta_1^2} + \left(\frac{T_1}{T_0}\right)^2 \frac{\beta_1^2}{1-(T_1/T_0)^2\beta_1^2}$$

ppm order  $< 10^{-6}$      $\sim 10^{-6}$      $\beta_1 \sim 10^{-4}$  ( $k \sim 10^{-2}$ )

under the isochronous condition of ppm order

# R3 : cyclotron-like lattice structure



## R3

### 24 rectangular dipoles

- Hexagonal symmetrical structure
- Circumference : 60.35 m
- Length of a straight section : 4.02 m
- Acceptance :
  - momentum :  $\pm 0.3\%$
  - transverse :  $20\pi / 10\pi$  mm·mrad
- Dispersion :  $\sim 70$  mm/% (typically)

### 10 trim-coils




### Injection line

- 10 quadrupoles
- 1 dipole


Selected RIs  
from BigRIPS

# R3 : cyclotron-like lattice structure




- R3**
- 24 rectangular dipoles
  - Hexagonal symmetrical structure
  - Circumference : 60.35 m
  - Length of a straight section : 4.02 m
  - Acceptance :
    - momentum :  $\pm 0.3\%$
    - transverse :  $20\pi / 10\pi$  mm·mrad
  - Dispersion :  $\sim 70$  mm/% (typically)

**10 trim-coils**



1 Injection septa  
2 Extraction septa

**Injection line**  
10 quadrupoles  
1 dipole



Selected RIs from BigRIPS

# Construction and Machine study

2012 - 2013



2014 - 2015

- Basic performance test of R3 using  $\alpha$ -source.
- Development of fast-kicker system (fast-response, fast-recharging) and beam diagnostic devices. (Resonant Schottky pick-up, C-foil + MCP)
- First commissioning of R3 using  $^{78}\text{Kr}$  beam was conducted on June 2015 and off-line analysis is in progress.

# Performance test of R3 using $\alpha$ -particles I

## R3 for $\alpha$ -particle

Betatron tune : 1.003  
Dispersion : 98 mm/%

Momentum slit  
 $dp/p = \pm 0.5\%$



$p_0 + \delta p$   $p_0$   $p_0 - \delta p$

C-foil ( $60 \mu\text{g}/\text{cm}^2$ )  
+MCP


Plastic scinti.  
25x50x5mm<sup>t</sup>



### First-order trim field : $(dB/dr)/B_0$ [1/m]





# Performance test of R3 using $\alpha$ -particles II




⊗ Time resolution of this detection system  $\sim 460$ ps

$(dB/dr)/B_0$  [ $m^{-1}$ ]

# Performance test of R3 using $\alpha$ -particles III




### Extraction (4.585 $\mu$ s/turn)



# Fast-kicker system



**Twin-type kicker magnet**  
13 cells for one side  
350 pF / cell, 100 nH / cell





# Fast-kicker system



**Twin-type kicker magnet**  
 13 cells for one side  
 350 pF / cell, 100 nH / cell

## Fast-recharging mechanism

new hybrid charging system  
 to extract as soon as possible  
 using same kicker magnet  
 of injection.



## Fast-response mechanism

new gate board for Thyatron  
 to excite a kicker magnet as fast as possible.

# Fast-recharging mechanism



## Hybrid charging system

### Main charger


- Half sinusoidal waveform
- 90% charging in 100 $\mu$ s

### Sub charger


- 500kHz resonance
- +10% charging within 100 $\mu$ s
- Keep  $V_C$  100 $\pm$ 1% to discharge at any time



## PFN charging waveform (1set)



# Beam diagnostic devices




## Monitor for checking of the injection trajectories

Plastic scintillation counters are installed on movable stage to each straight section


# Beam diagnostic devices

Monitor for tuning of isochronism  
Resonant Schottky pick-up

Monitor for checking of the injection trajectories  
Plastic scintillation counters are installed on movable stage to each straight section




Resonance frequency :	173MHz (TM <sub>010</sub> )
Tuning range :	±1.5MHz
Shunt Impedance $R_{sh}$ :	161kΩ
Quality factor $Q_0$ :	1880
Ceramic tube size :	290mmΦ, 15mm thickness




# Beam diagnostic devices

Monitor for tuning of isochronism  
Resonant Schottky pick-up

Monitor for checking of the injection trajectories  
Plastic scintillation counters are installed on movable stage to each straight section




Resonance frequency :	173MHz (TM <sub>010</sub> )
Tuning range :	±1.5MHz
Shunt Impedance $R_{sh}$ :	161kΩ
Quality factor $Q_0$ :	1880
Ceramic tube size :	290mmΦ, 15mm thickness




# Beam diagnostic devices

Monitor for tuning of isochronism  
Resonant Schottky pick-up

Monitor for checking of the injection trajectories  
Plastic scintillation counters are installed on movable stage to each straight section




Resonance frequency :	173MHz (TM <sub>010</sub> )
Tuning range :	±1.5MHz
Shunt Impedance $R_{sh}$ :	161kΩ
Quality factor $Q_0$ :	1880
Ceramic tube size :	290mmΦ, 15mm thickness



# Beam diagnostic devices

## Monitor for tuning of isochronism

Resonant Schottky pick-up




Resonance frequency : 173MHz (TM<sub>010</sub>)  
Tuning range : ±1.5MHz  
Shunt Impedance  $R_{sh}$  : 161kΩ  
Quality factor  $Q_0$  : 1880  
Ceramic tube size : 290mmΦ, 15mm thickness

## Monitor for checking of the injection trajectories

Plastic scintillation counters are installed on movable stage to each straight section

## Monitor for circulating particle

C-foil + MCP timing monitor



C-foil (60μg/cm<sup>2</sup>)  
MCP secondary electron detector  
Window size : 100×50 mm<sup>2</sup>  
Position sensitivity : less than 10mm  
Efficiency : ~ 75 %  
Time resolution :  $\sigma \sim 130$ ps  
with <sup>84</sup>Kr 200MeV/u

# First commissioning of R3 using $^{78}\text{Kr}$ beam

## Items

0. Beam transport
1. Individual injection using self-trigger mechanism
2. Detect the circulating particles using C-foil + MCP
3. Extraction the circulating particles
4. Isochronous condition with TOF vs. F6x information
5. Resonant Schottky pick-up with single  $^{78}\text{Kr}$  ion


## Beam conditions

- Energy : 345 MeV/u  $\rightarrow$  168 MeV/u @R3
- Injection repetition rate :  $\sim 90$  Hz (@F3 circuit)


## Ring conditions

- Transition  $\gamma_{\text{tr}}$  : 1.18
- Betatron tune :  $\nu_x = 1.18, \nu_y = 0.93$
- $\beta$  function :  $\beta_x = 8.4$  m,  $\beta_y = 11.9$  m
- Dispersion : 70 mm/%
- Kick angle :  $\sim 11$  mrad




# 1. Individual injection [Proposed by I. Meshkov NIMA523\(2004\)262](#)



## 2. Detect the circulating particles




## 2. Detect the circulating particles




TDC (Aquiris TC890)  
→ 379.65 ns / turn

✂ Useful information  
for determining  
the resonance frequency  
of Schottky pick-up.

# 3. Extraction




Count rate @plastic [cps]




## TOF spectra

for the difference extraction timing





ELC



# 4. Isochronous condition

First-order trim field :  $(dB/dr)/B_0=0.277$

Magnetic field distribution





# 4. Isochronous condition

First-order trim field :  $(dB/dr)/B_0=0.277$

↓  
0.279




Magnetic field distribution



# 4. Isochronous condition


- Extractable momentum width :  $\pm 0.2\%$
- Degree of isochronism :  $\sim 3.5 \times 10^{-5}$  (10-ppm order including the tail)

## Result of numerical analysis




## 5. Resonant Schottky pick-up (in storage mode)

- Succeeded in detecting the single  $^{78}\text{Kr}^{36+}$  ion  $\rightarrow$  [high sensitivity](#)
- Frequency resolution :  $\sim 1.3 \times 10^{-6}$  (FWHM)  $\rightarrow$  [enough resolution](#)
- Stored in the ring about 4 seconds while changing its frequency due to the poor degree of vacuum in the ring.
- The shape of curve indicates the isochronous condition.



※ 34 events in total !  
(stored time > 1 sec.)

# Preliminary consideration




Harmonics : 66  
Turn number : 1850  
Main residual gas : H<sub>2</sub>O (assumption)  
Pressure :  $\sim 4 \times 10^{-5}$  Pa (used the worst case)

# Summary

- First commissioning using  $^{78}\text{Kr}$  beam was conducted successfully.
- First-order trim field can adjust the isochronism in an order of 10-ppm.
- For adjusting the isochronism in an order of ppm. Resonant Schottky pick-up can be used for checking it.

## Result of numerical analysis



## Next beam commissioning is scheduled in Dec. 2015.

- Verification of the principle of relative mass measurements  
Primary beam :  $^{48}\text{Ca}$  345 MeV/u  
Secondary particles :  $^{38}\text{K}$ ,  $^{40}\text{Ca}$ ,  $^{36}\text{Ar}$ ,  $^{39}\text{K}$ ,  $^{37}\text{Ar}$ , etc...

## We will start mass measurement experiments from 2016.

# Thank you for your attention

Project leader : T. Uesaka chief scientist

Nishina Center

Operation, Maintenance,  
Development

Accelerator  
Group.

BigRIPS  
Team

M. Wakasugi  
Y. Yamaguchi, Y. Abe

S. Naimi, D. Nagae  
F. Suzuki, G. Zhuang  
S. Omika, H. Miura

Spin-isospin lab.

University,  
Institute

- Univ. of Tsukuba
- Saitama Univ.
- Nagaoka Univ. of Tech.
- PPJ Ltd.
- CNS
- GSI in Germany
- IMP in China

# Prospects

R3 will be improved as a **ppm-order machine** in a few years.  
→ precision mass measurement even only one event / day

Resonant Schottky pick-up  
→ lifetime measurements  
of rare-RIs

In the future:  
Nuclear reaction study of rare-RIs  
will be performed at R3  
with help of beam cooling !

