

Design of LINAC-100 and LINAC-30 for new rare isotope facility project DERICA at JINR

L.V. Grigorenko¹, A.S. Fomichev¹, V.S. Duybkov², T.V. Kulevoy^{2,3},
Yu. Yu. Lozeev², T.A. Lozeeva², S.M. Polozov², A.V. Samoshin²

¹Joint Institute for Nuclear Research, Dubna, Russia

²National Research Nuclear University - Moscow Engineering
Physics Institute, Moscow, Russia

³NRC Kurchatov Institute – Institute of Theoretical and Experimental
Physics, Moscow, Russia

Contents:

- DERICA (Dubna Electron – Radioactive Ion Collider fAcility) project at JINR:
motivation, physical aims, general structure and site
- LINAC-100 initial layout and beam dynamics
- LINAC-30 initial layout
- DERICA: possible collaboration
- Conclusions





What is at JINR (Flerov Lab.) today

Elements 102 - 108 and 113 - 118
were synthesized at FLNR JINR

Superheavy "isle of stability"
discovered

New elements

^{114}Fl Flerovium
 ^{116}Lv Livermorium
 ^{113}Nh Nihonium
 ^{115}Mc Moscovium
 ^{117}Ts Tennessine
 ^{118}Og Oganesson
recognized recently



Fragment-separator
ACCULINNA:
Studies of the light RIBs

The only facility for RIB
studies in Russia, CIS, and
Eastern Europe

7-year planning prospects

**"Factory of
 superheavy
 elements"**

Stage: mounting of
 equipment

Investment: ~55 M€

Near future

Cn

118

114

162

82 Pb

126

???

Long-time
 prospects

100 Sn

50 Sn

82

132 Sn

48 Ni

28 Ni

20 Ca

8 O

Near future

78 Ni

50

20


28

8

Facility based on
ACCULINNA-2 fragment-separator
 Stage: first experiments in 2018
 Investment: ~10 M€


DERICA - Dubna Electron – Radioactive Ion Collider Facility – project of RIB-factory for rp-process study

General layout



DERICA - Dubna Electron – Radioactive Ion Collider Facility – project of RIB-factory for rp-process study


General layout



~~TSR/ISOLDE@CERN~~

~~ELISe/NESR@F~~
~~AIR~~

ESR/CRYRING@
GSI





~~HIRFL-
CSR@Lanzhou~~

HIAF

~~MUSES@RIK
EN~~

RI-
Ring@RIKEN




- A lot of ring projects – serious interest to the topic
- All the ring projects with e-collider abilities were cancelled or indefinitely postponed


Why it has happened this way?

~~TSR/ISOLDE@CERN~~

~~ELISE/NESR@F
AIR~~




~~HIREL-
CSR@Lanzhou~~



Not in sale



Yu.Ts. Oganessian *et. al.*,
Z. Phys. A341 (1992) 217




– All the ring projects with e-collider abilities
were cancelled or indefinitely postponed

– serious interest to the

- **DERICA site**



- LINAC-100 initial layout and beam dynamics



First version of DERICA's driver LINAC-100 general layout

The supposed primary beams in the LINAC-100 accelerator. The most available charges of Bi and U correspond to modern capacities of the intensive cryogenic ECR sources.

Ion	A/Z	I , μA
$^{11}\text{B}^{2+}$	5.5	> 10
$^{18}\text{O}^{3+}$	6.0	> 10
$^{20,22}\text{Ne}^{4+}$	5.5	> 8
$^{32,36}\text{S}^{6+}$	6.0	> 5
$^{36}\text{Ar}^{6+}$	6.0	> 5
$^{40,48}\text{Ca}^{7+}$	6.0	> 5
$^{56,64}\text{Ni}^{11+}$	5.8	> 5
$^{86}\text{Kr}^{15+}$	5.7	5
$^{132}\text{Xe}^{22+}$	6.0	5
$^{160}\text{Gd}^{27+}$	5.9	5
$^{209}\text{Bi}^{37+}$	5.65	4
$^{238}\text{U}^{40+}$	5.95	$\sim 0.8^*$

Base parameters of LINAC-100 RFQ both for 81 and 162 MHz


Operating frequency, MHz	162.5	81.25
Input energy, keV/u	16.9	16.3
Output energy, keV/u	612	614
Max modulation	1.4	1.9
Aperture, mm	3.2	4.4
Transmission, %	> 98	99.8
Synchr. Phase, grad.	-90 ... -30	-90 ... -30
Voltage, kV	100	100
Input beam emittance, mm*mrad	200	200
Length, cm	600	600

Base parameters of LINAC-100 RFQ both for 81 and 54 MHz

54 MHz


???






Operating frequency, MHz	162.5	
Input energy, keV/u	16.9	
Output energy, keV/u	612	614
Max modulation	1.4	1.9
Aperture, mm	3.2	4.4
Transmission, %	> 98	99.8
Synchr. Phase, grad.	-90 ... -30	-90 ... -30
Voltage, kV	100	100
Input beam emittance, mm*mrad	200	200
Length, cm	600	600








$f=162.5$ MHz

$f=81.25$ MHz












The design of RFQ cavity will be based on the CW segmented-vane RFQ [V.A. Andreev, G. Parisi. Proc. Of PAC'93, 3124-3126 (1994)] developed by the joint team of MEPhI, ITEP, GSI and HIM: [S. Polozov et al., Proc. of HB'16, 188-190 (2016); S. Polozov et al., Proc. of RuPAC'16, 267-269 (2016); S. Polozov et al., Proc. of IPAC'17, 1333-1336 (2017)]

Normal conducting cavities for intermediate energies

As known, the intermediate energy band (after RFQ and up to 2.0-2.5 MeV/u) has some difficulties both for the beam dynamics and the RF efficiency of the accelerating cavities.


RF Crossed Lenses / modified electrode form RFQ / 3-cell or 5-cell CH/IH cavities ?



A.I. Balabin, G.N. Kropachev NIM A, 459, 87-92 (2001).

A.S. Plastun, A.A. Kolomiets Proc. of LINAC'12, 41 – 43 (2012).

*High energy linac part: SC cavities **



5 groups

156 cavities

140 m

BEAMDULAC-SCL code simulations

*** Current SRF
activities in
Russia:
S.M. Polozov,
Tua2wc02**

Group	1	2	3	4	5	6
W_{in} , MeV/u	1.5	3.16	6.59	13.78	29.24	63.8
β_{in}	0.056	0.08	0.12	0.170	0.244	0.351
β_g	0.069	0.01	0.144	0.207	0.298	0.428
W_{out} , MeV/u	3.16	6.59	13.78	29.24	63.8	100.0
β_{out}	0.082	0.12	0.170	0.244	0.351	0.428
T , %	20	20	20	20	20	20
f , MHz	162	162	162	324	324	324
ϕ_{inj} , deg	-30	-30	-30	-30	-27	-20
U , MV	0.52	1.5	2.7	3.0	6.0	9.5
E , kV/cm	2	4	5.1	7.83	10.9	11.93
N_{gap}	4	4	4	4	4	4
L_{cav} , m	0.257	0.37	0.532	0.383	0.551	0.796
B_{sol} , T	3.1	4.5	5.5	6	7	7.5
L_{sol} , m	0.2	0.2	0.2	0.2	0.2	0.2
L_{per} , m	0.657	0.77	0.932	0.783	0.951	1.196
N_{per}	22	16	18	36	40	24
K_T , %,	100	100	100	100	100	100








Group	1	2	3	4	5	6
W_{in} , MeV/u	1.5	3.16	6.59	13.78	29.24	63.8
β_{in}	0.056	0.08	0.12	0.170	0.244	0.351
β_g	0.069	0.01	0.144	0.207	0.298	0.428
W_{out} , MeV/u	3.16	6.59	13.78	29.24	63.8	100.0
β_{out}	0.082	0.12	0.170	0.244	0.351	0.428
T , %	20	20	20	20	20	20
f , MHz	162	162	162	324	324	324
ϕ_{inj} , deg	-30	0	0	0	0	0
U , MV	0.52	1.04	1.58	2.12	2.66	3.20
E , kV/cm	2	4	5.1	7.83	10.9	11.93
N_{gap}	4	4	4	4	4	4
L_{cav} , m	0.257	0.37	0.532	0.383	0.551	0.796
B_{sol} , T	3.1	4.5	5.5	6	7	7.5
L_{sol} , m	0.2	0.2	0.2	0.2	0.2	0.2
L_{per} , m	0.657	0.77	0.932	0.783	0.951	1.196
N_{per}	22	16	18	36	40	24
K_T , %	100	100	100	100	100	100

Injection energy should be increased

Group	1	2	3	4	5	6
W_{in} , MeV/u	1.5	3.16	6.59	13.78	29.24	63.8
β_{in}	0.056	0.08	0.12	0.170	0.244	0.351
β_g	0.069	0.01	0.144	0.207	0.298	0.428
W_{out} , MeV/u	3.16	6.59	13.78	29.24	63.8	100.0
β_{out}	0.082	0.12	0.170	0.244	0.351	0.428
T , %	20	20	20	20	20	20
f , MHz	162	162	162	324	324	324
ϕ_{inj} , deg	-30	-30	-30	-30	-30	-30
U , MV	0.52	0.52	0.52	0.52	0.52	0.52
E , kV/cm	2	4	5.1	7.83	10.9	11.93
N_{gap}	4	4	4	4	4	4
L_{cav} , m	0.257	0.37	0.532	0.383	0.551	0.796
B_{sol} , T	3.1	3.1	3.1	3.1	7	7.5
L_{sol} , m	0.2	0.2	0.2	0.2	0.2	0.2
L_{per} , m	0.657	0.77	0.932	0.783	0.951	1.196
N_{per}	22	16	18	36	40	24
K_T , %	100	100	100	100	100	100

Injection energy should be increased

Stripper is necessary




•LINAC-30 initial layout: ions

Representative secondary radioactive isotopes for LINAC-30


Ion	Possible A	Charge	A/Z band
B	8 – 19	5+	1.6 – 3.8
O	13 – 24	8+	1.63 – 3.0
Ar	31 – 46	16+	1.94 – 2.88
Sn	100 – 132	38+	2.63 – 3.47

$A/Z=1.6 - 3.8$!!!


•LINAC-30 initial layout



OR ???




•DERICA: possible collaboration (accelerators)



•Conclusions

- DERICA: **D**ubna **E**lectron – **R**adioactive **I**on **C**ollider **f**Acility is the new ambitious RIB project from Russia
- The project aims, DERICA's possible site and the general layout are initially defined
- LINAC-100 design and beam dynamics simulations are started
- LINAC-30: normal conducting or superconducting?
- SRF program is under start
- We are open for new collaboration

Thank You for attention !



**A number of
additional slides**


Radioactive Ion Beam (RIB) physics

The map of nuclides

- 254 stable nuclides,
- 339 can be found in nature
- Around 3100 RI are known
- Around 2500 to be discovered

**“Isle of stability”
for superheavies:**
We just
“touched” a bit of
its “shore”...

**Proton
dripline:**
Achieved and
studied for
 $Z < 32$




**Limits of nuclear
structure existence:**
Are known only for
the lightest nuclei

**Exotic structure of exotic
nuclides:**

- Neutron/proton halo
- Neutron skin
- “Soft” excitation modes
- Breakdown of shell structure
- New “magic numbers”


Neutron dripline:
Achieved and studied for
 $N < 20$

Motivation – Applications to nucleosynthesis



- Hydrostatic burning – slow process
- Explosive burning – rapid processes
- Where does it take place?
- Every day observed violent events in space are produced by rp-processes
- Element abundance in space is connected with r-processes
- No quantitative understanding until the driplines are studied in details

DERICA general layout



• DERICA Stages

Stage 0: the scientific agenda is fully formulated, the technical concept is formed, required R&Ds are carried out.

Stage 1: equipment of the {gas cell - ion trap - ion source/charge breeder} system; experiments with stopped RI in the electromagnetic traps; construction and commissioning of LINAC-30.

Stage 2: LINAC-100 construction and commissioning; applied studies with high-intensity stable-ion beams; DFS construction and commissioning;

Stage 3: gas cell construction; system {gas cell - ion trap - ion source/charge breeder} is relocated to DFS; LINAC-30 is relocated to the DFS; FRR construction and commissioning;

Stage 4: CR and ER construction and commissioning; experiments can be performed at three independent experimental locations of the CR ring.

Stage #: LINAC-100 energy upgrade (150-100 MeV).