

THPV021 TATU: A FLEXIBLE FPGA-BASED TRIGGER AND TIMER UNIT CREATED ON CompactRIO FOR THE FIRST SIRIUS BEAMLINES



MINISTRY OF SCIENCE, TECHNOLOGY AND INNOVATIONS



J. R. Piton, D. Alnajjar, D. H. C. Araujo, J. L. Brito Neto, L. P. do Carmo, L. C. Guedes, M. A. L. de Moraes, Brazilian Synchrotron Light Laboratory (LNLS), Campinas, Brazil

ICALEPCS 2021

THPV021

The problem

Synchronizing devices, e.g. in a quick scanning operation ("fly-scan")

ICALEPCS 2021

Tatu as a MASTER signal generator

Tatu as a FOLLOWER and a signal distributor

THPV021

Premises for Tatu

- Pulses up to 4 kHz, combined and configurable by software
- EPICS as the control platform

- at least one CompactRIO unit available, per beamline hutch (904x, 40 MHz FPGA clock and Linux RT)
- ancillary small code could run in the same CRIO chassis

ICALEPCS 2021

THPV021

Tatu management

MASTER PULSE mode

Input port acquisition
Ports IO0 to IO3 (IO8 to IO11, IO16 to IO19)

Event detection (trigger)
P0 to P3 (P8 to P11, P16 to P19)

Output Generation
Ports IO4 to IO7 (IO12 to IO15, IO20 to IO23)

Forced Trigger

Tatu as MASTER
(5 points, 1 per ms)
4 output portas
Pulsed width: 150 μs

ICALEPCS 2021

THPV021

An example of use

```

$ caput MNC:B:RIO01:9401H:Activate Off (or: 0)
$ caput MNC:B:RIO01:9401H:MasterMode On (or: 1)
$ caput MNC:B:RIO01:9401H:ZeroPulses On (or: 1)
$ caput MNC:B:RIO01:9401H:MasterPulseNumber 10
$ caput MNC:B:RIO01:9401H:MasterPulseLength 1000
$ caput MNC:B:RIO01:9401H:MasterPulsePeriod 500000


$ caput MNC:B:RIO01:9401H:InputTriggerIO0 Follower (or: 7)
$ caput MNC:B:RIO01:9401H:ConditionIO7:c0 Master pulse (or: 2)
$ caput MNC:B:RIO01:9401H:OutputIO7:c0 Rising pulse (or: 4)
$ caput MNC:B:RIO01:9401H:PulseIO7:c0 200
$ caput MNC:B:RIO01:9401H:DelayIO7:c0 50

$ caput MNC:B:RIO01:9401H:Activate On (or: 1)
    
```

ICALEPCS 2021


The problem

Synchronizing devices,
e.g. in a quick scanning
operation ("fly-scan")




TTL
signals

Tatu as a MASTER signal generator



Tatu as a FOLLOWER and a signal distributor



Premises for Tatu




- Pulses up to 4 kHz, combined and configurable by software



- at least one CompactRIO unit available, per beamline hutch (904x, 40 MHz FPGA clock and Linux RT)




- EPICS as the control platform



- ancillary small code could run in the same CRIO chassis


Tatu management




Forced Trigger

Tatu as **MASTER**
(5 points, 1 per ms)
4 output portas

Pulsed width: 150 μ s



An example of use



```
$ caput MNC:B:RIO01:9401H:Activate Off (or: 0)
```

```
$ caput MNC:B:RIO01:9401H:MasterMode On (or: 1)
```

```
$ caput MNC:B:RIO01:9401H:Zeropulses On (or: 1)
```

```
$ caput MNC:B:RIO01:9401H:MasterPulseNumber 10
```

```
$ caput MNC:B:RIO01:9401H:MasterPulseLength 1000
```

```
$ caput MNC:B:RIO01:9401H:MasterPulsePeriod 500000
```

```
$ caput MNC:B:RIO01:9401H:InputTriggerIO0 Follower (or: 7)
```

```
$ caput MNC:B:RIO01:9401H:ConditionIO7:c0 Master pulse (or: 2)
```

```
$ caput MNC:B:RIO01:9401H:OutputIO7:c0 Rising pulse (or: 4)
```

```
$ caput MNC:B:RIO01:9401H:PulseIO7:c0 200
```

```
$ caput MNC:B:RIO01:9401H:DelayIO7:c0 50
```

```
$ caput MNC:B:RIO01:9401H:Activate On (or: 1)
```