

# VERY FIRST EXPERIENCE WITH THE STANDARD DIAGNOSTICS AT THE EUROPEAN XFEL

D. Lipka\* on behalf of the European XFEL Diagnostics team, DESY, Hamburg, Germany

## Abstract

The whole European XFEL becomes in operation this year. Dedicated standard diagnostics systems are installed and almost all types are tested at the injector before. Now the standard diagnostics are used to commission the facility. In this contribution the very first results and the operation experiences of the standard electron beam diagnostics of the entire European XFEL are reported.

## INTRODUCTION

The European X-ray Free-Electron Laser (EU-XFEL) [1, 2] is the 3.4 km long international facility, running from DESY in Hamburg to the town of Schenefeld (Schleswig-Holstein) in Germany, see Fig. 1. To construct and operate the EU-XFEL, international partners agreed on the foundation of an independent research organization – a non-profit limited liability company under German law named the European XFEL GmbH. DESY is leading the accelerator construction consortium and will be in charge of the accelerator operation.

The accelerator is based on superconducting TESLA Radio-Frequency (RF) technology. Within one RF pulse of up to 600  $\mu$ s length, a train with up to 2700 bunches can be generated. This results in a bunch minimal spacing of 222 ns. The repetition rate of the RF pulses is 10 Hz, so that a maximum number of 27000 X-ray pulses per second can be produced. The beam charge varies from 20 pC to 1 nC to provide different characteristics of the output radiation, i. e. the average power or the bunch length, as requested by the users. Therefore diagnostics components have to monitor the beam properties within this dynamic range.

Beam operation of the photocathode gun started already in February 2015, the complete injector became operable in December 2015 and beam characterization with optimization take place until July 2016 [3]. A description of the injector operation with the standard diagnostics is presented in [4]. The cooldown of the main accelerator was finished end of 2016. In January 2017 beam operation after the injector started: the transmission was established step by step to each dump in the two successively bunch compressors and in the following up to the first main dump at Osdorf site (about 2100 m behind the electron source) in January and February 2017, compare with Fig. 1. End of April the beam was transmitted through two SASE sections, these sections installed serially after another. First lasing was performed beginning of May. Along the complete electron beamline several diagnostics systems are installed, commissioned and have been optimized for the measurement of the electron beam properties. This paper focuses on standard electron

beam diagnostics for the EU-XFEL. Special and higher-order mode diagnostics systems are described in [5–12].

## STANDARD DIAGNOSTICS FOR THE EUROPEAN XFEL

The standard diagnostics contains a variety of charge, position, loss monitors and screen stations. It is also planned to use wire scanners at positions with high electron energies. The list of monitoring systems is given in Table 1. A description of the different systems with results of their laboratory and beam tests can be found in [13–27].

### Charge Monitors

Toroid are used consisting of a ferrite core with windings around a ceramic gap in the pipe and are distributed along the beamlines [13]. During beam commissioning these monitors started in a self-trigger mode to detect the beam independently from the timing system; this feature is useful to detect the first beam and measure the delay between beam and trigger signal. In the following the trigger mode is enabled to improve the performance. The beam position monitors (BPM) are providing the charge signals too. In the Figure 2 the transmission is shown with the Toroids and BPMs from the injector to the dump after two SASE sections; a beamline length of about 3.1 km. The Toroid charge values differ only by max. 3% therefore the laboratory calibration has this relative accuracy. The charge calibration from the BPMs are used from the experience during the injector operation, still some discrepancies are seen; these will be corrected. In addition the Toroids generate a history of the beam arrival time in sub-nanosecond range to verify that the photocathode-laser hits the correct RF-bucket. This was used to correct the timing of the laser after maintenance. Faraday cups and dark current monitors [14] are used to measure the charge as well. The later is able to detect even charge values below pC.

Table 1: Diagnostics system numbers for the complete EU-XFEL and for the gun with injector

System	Total number	Gun and injector
Charge monitors	~50	10
BPMs	~460	14
Screens	~70	11
Wire scanners	12	0
Loss monitors	~490	20

\* dirk.lipka@desy.de






Figure 3: Resolution measurement result of the BPMs from the injector on the left to the first main dump before the SASE sections on the right. Upper plot: charge reading; middle plot: vertical position data; lower plot: vertical resolution. Different kind of BPMs deliver different resolution. Colors: red - buttons, green - reentrant, blue - cavities.




Figure 4: Display of the transverse beam distribution with a screen station at 1995 m behind the electron source during the first beam commissioning.

ionization chambers [26]. They are capable to detect both beam losses on a bunch-by-bunch basis and dark current. Diamond sensors provide higher sensitivity, whereas sapphire sensors remain operational at higher intensities of impinging particles. Both kind of sensors showed the halo of charged particles accordingly to their sensitivities and used to prevent high losses before the dump to provide safe beam operation.

### Dosimetry

To protect the electronics and undulators the  $\gamma$  radiation is measured due to RadFets with rack-internal and external sensors [27]. During the operation these sensors became operational and measured the radiation which was correlated with the number of bunches in the train because higher number of bunches caused a higher accumulated dose.

## SUMMARY

The standard diagnostics of the EU-XFEL has been ready for beam property measurements since the first day of beam operation. BPMs and Toroids can be used in self-trigger as well as in externally-triggered mode, the measured resolution fulfill the requirements. The dark current monitors are useful to measure both, dark current and beam charge. Online monitors of beam loss, halos and radiation dose are installed and operational. Screen stations are used with on- and off-axis screens. The latter one is useful during long bunch train operation to prove the beam properties during user operations by observing one bunch out of the whole train.

## OUTLOOK

The diagnostics for the third SASE section will be installed in the next months and becomes in operation in autumn this year.

## ACKNOWLEDGEMENT

The authors thank all colleagues who contributed to this project; special thanks to M. Guetg who updated the resolution measurement program.

Note: half filled screens (off-axis screens) are available as well at the diagnostics stations of the injector and bunch compressors to measure the transverse beam distribution of kicked bunches. This is useful to characterize the beam properties during long bunch train operations where only one bunch is kicked. This was done successfully during the beam characterization.

### Beam Loss and Halo Monitors

The beam loss monitors (BLM) are based on scintillators read out by photomultipliers [25]. The 490 BLMs are distributed along the electron beamline of the EU-XFEL. They generate alarms to stop the beam operations based on dark current or single bunch losses when a threshold is exceeded. During operation these monitors were intensively used to prevent losses. Beam Halo monitors (BHM) are installed in front around the dump vacuum chambers and consist of four diamond and four sapphire sensors operating as solid-state

## REFERENCES

- [1] M. Altarelli *et al.*, “The European X-Ray Free-Electron Laser”, technical design report, 2007, <http://www.xfel.eu/en/documents/>
- [2] W. Decking, “Commissioning of the European XFEL”, this proceedings IPAC 2017.
- [3] F. Brinker *et al.*, “Commissioning of the European XFEL Injector”, proceedings of IPAC 2016, <http://accelconf.web.cern.ch/AccelConf/ipac2016/papers/tuoca03.pdf>
- [4] D. Lipka *et al.*, “First Experience with the Standard Diagnostics at the European XFEL Injector”, proceedings of IBIC 2016, <http://ibic2016.vrws.de/papers/mob102.pdf>
- [5] C. Gerth, “Electron Beam Diagnostics for the European X-Ray Free-Electron Laser”, proceedings of DIPAC 2007, <http://accelconf.web.cern.ch/AccelConf/d07/papers/moo2a02.pdf>
- [6] M. Roehrs and C. Gerth, “Electron Beam Diagnostics with Transverse Deflecting Structures at the European X-Ray Free Electron Laser”, proceedings of FEL 2008, <http://accelconf.web.cern.ch/AccelConf/FEL2008/papers/mopph049.pdf>
- [7] J. Wychowaniak *et al.*, “Design of TDS-based Multi-screen Electron Beam Diagnostics for the European XFEL”, proceedings of FEL 2014, <http://accelconf.web.cern.ch/AccelConf/FEL2014/papers/thp075.pdf>
- [8] M. K. Czwalinna *et al.*, “New Design of the 40 GHz Bunch Arrival Time Monitor Using MTCA.4 Electronics at FLASH and for the European XFEL”, proceedings of IBIC 2013, <http://accelconf.web.cern.ch/AccelConf/IBIC2013/papers/wepc31.pdf>
- [9] K. P. Przygoda *et al.*, “MicroTCA.4 Based Optical Front-end Readout Electronics and Its Applications”, proceedings of IBIC 2016, <http://ibic2016.vrws.de/papers/mopg13.pdf>
- [10] M. Yan and C. Gerth, “Single-bunch Longitudinal Phase Space Diagnostics in Multi-bunch Mode at the European XFEL”, proceedings of IBIC 2013, <http://accelconf.web.cern.ch/AccelConf/IPAC2013/papers/mopme012.pdf>
- [11] N. Baboi *et al.*, “HOM Characterization for Beam Diagnostics at the European XFEL Injector”, proceedings of IBIC 2016, <http://ibic2016.vrws.de/papers/wepg03.pdf>
- [12] M. Scholz, M. Hamberg, F. Brinker, “Commissioning and First Heating with the European XFEL”, this proceedings IPAC 2017.
- [13] M. Werner *et al.*, “A Toroid Based Bunch Charge Monitor System with Machine Protection Features for FLASH and XFEL”, proceedings of IBIC 2014, <http://accelconf.web.cern.ch/AccelConf/IBIC2014/papers/wepf02.pdf>
- [14] D. Lipka *et al.*, “Dark Current Monitor for the European XFEL”, proceedings of DIPAC 2011, <http://accelconf.web.cern.ch/AccelConf/DIPAC2011/papers/weoc03.pdf>
- [15] M. Stadler *et al.*, “Low-Q Cavity BPM Electronics for E-XFEL, FLASH-II and SwissFEL”, proceedings of IBIC 2014, <http://accelconf.web.cern.ch/AccelConf/IBIC2014/papers/wepd12.pdf>
- [16] D. Lipka *et al.*, “Development of Cavity BPM for the European XFEL”, proceedings of LINAC 2010, <http://accelconf.web.cern.ch/AccelConf/LINAC2010/papers/tup094.pdf>
- [17] D. M. Treyer *et al.*, “Design and Beam Test Results of Button BPMs for the European XFEL”, proceedings of IBIC 2013, <http://accelconf.web.cern.ch/AccelConf/IBIC2013/papers/wepc21.pdf>
- [18] C. Simon *et al.*, “New Electronics Design for the European XFEL Re-entrant Cavity Monitor”, proceedings of IBIC 2012, <http://accelconf.web.cern.ch/AccelConf/IBIC2012/papers/mopa15.pdf>
- [19] C. Simon *et al.*, “Production Process for the European XFEL Re-Entrant Cavity BPM”, proceedings of IBIC 2014, <http://accelconf.web.cern.ch/AccelConf/IBIC2014/papers/tupf05.pdf>
- [20] C. Simon *et al.*, “Design and Beam Test Results of the Reentrant Cavity BPM for the European XFEL”, proceedings of IBIC 2016, <http://ibic2016.vrws.de/papers/tupg17.pdf>
- [21] C. Wiebers *et al.*, “Scintillating Screen Monitors for Transverse Electron Beam Profile Diagnostics at the European XFEL”, proceedings of IBIC 2013, <http://accelconf.web.cern.ch/AccelConf/IBIC2013/papers/wepf03.pdf>
- [22] G. Kube *et al.*, “Transverse Beam Profile Imaging of Few-Micrometer Beam Sizes Based on a Scintillator Screen”, proceedings of IBIC 2015, <http://accelconf.web.cern.ch/AccelConf/IBIC2015/papers/tupb012.pdf>
- [23] T. Lensch *et al.*, “Wire Scanner Installation into the MicroTCA Environment for the European XFEL”, proceedings of IBIC 2014, <http://accelconf.web.cern.ch/AccelConf/IBIC2014/papers/mopf13.pdf>
- [24] V. Gharibyan *et al.*, “Twisting Wire Scanner”, proceedings of IBIC 2012, <http://accelconf.web.cern.ch/AccelConf/IBIC2012/papers/thcb02.pdf>
- [25] A. Kaukher *et al.*, “XFEL Beam Loss Monitor System”, proceedings of BIW 2012, <http://accelconf.web.cern.ch/AccelConf/BIW2012/papers/mopg007.pdf>
- [26] A. Ignatenko *et al.*, “Beam Halo Monitor for FLASH and the European XFEL”, proceedings of IPAC 2012, <http://accelconf.web.cern.ch/AccelConf/IPAC2012/papers/moppr018.pdf>
- [27] F. Schmidt-Foehre *et al.*, “Commissioning of the New Online-Radiation-Monitoring-System at the New European XFEL Injector with First Tests of the High-Sensitivity-Mode for Intra-Tunnel Rack Surveillance”, proceedings of IBIC 2015, <http://accelconf.web.cern.ch/AccelConf/IBIC2015/papers/wecla02.pdf>
- [28] B. Keil *et al.*, “The European XFEL Beam Position Monitor System”, proceedings of IPAC 2010, <http://accelconf.web.cern.ch/AccelConf/IPAC10/papers/mope064.pdf>