

ORBIT simulation, measurement and mitigation of Transverse Beam Instability in the Presence of Strong Space Charge in the 3-GeV RCS of J-PARC

Pranab K. Saha, Y.Shobuda, H. Hotchi, H. Harada,
F. Tamura, N. Hayashi

2018/May/01

Intl. Particle Accelerator Conference (IPAC18), Vancouver, Canada

**J-PARC
(KEK & JAEA)**

400 MeV H⁻ Linac


**3 GeV Rapid Cycling
Synchrotron (RCS)**

**Neutrino Beam Line
to Kamioka (NU)**

**50 GeV Main Ring
Synchrotron (MR)
[30 GeV at present]**

**Materials & Life
Science Facility
(MLF)**



**Hadron
Experimental
Hall (HD)**



Outline:

1. Introduction of J-PARC RCS, Kicker Impedance and Motivation of the present study
2. Beam instability up to 0.5 MW beam power
3. Space Charge effect on the Beam Instability
4. Beam instability suppression strategy at 1 MW
-- Simulation and measurement results
5. Summary and Outlook

1. Introduction of 3-GeV RCS




To reduce the space charge effect longitudinal painting (LP) and transverse painting (TP) at injection are adopted.
 $\epsilon_{tp} = 100\pi$ mm mrad in this study


Parameter	Value	
Circumference [m]	348.333	
Repetition [Hz]	25	
Harmonic no, bunches	2, 2	
Protons/pulse (PPP)	8.33E13	
Beam power [MW]	1	
	Injection	Extraction
Energy [GeV]	0.4	3
f_0 [MHz]	0.614	0.84
$\Delta p/p$ [99%]	0.8	0.4
τ_z (bunch length) [m]	160	60
ν_s (synchrotron tune)	0.006	0.0005
ν_x, ν_y (betatron tune)	6.45, 6.42	Variable
$\xi_{x'}, \xi_{y'}$ (Nat. chromaticity)	-10, -7	Variable
B_f (Bunching factor)	0.47	0.21
$\Delta v_{incoh}, \Delta v_{coh}$	-0.3, -0.03	-0.05, -0.005

RCS Beam power at present:
To MLF: 0.5 MW; To MR: ~0.8 MW-eqv.



1. RCS Kicker Impedance



**×10 of SNS
KM impedance!**



Horizontal impedance of one KM
Y. Shobuda et al., NIMA 713, 52 (2013)



The impedances are also time dependent, higher w.r.t. energy.

– *Should be properly implementation in the simulation code*

-- Done

Motivation

■ R&D studies to reduce the KM impedance are in progress, but long way to go for realistic implementation.

■ Theoretical works provide overview (threshold) of the beam instability, but **realistic strategy for the beam instability suppression should be determined by detailed simulation studies.**

■ The space charge effect (SC) on the beam instability should be considered seriously.

-- ORBIT 3D SC code is used. We should determine realistic parameters to accomplish 1 MW beam power.

© We enhanced ORBIT by implementing all realistic time dependent machine parameters:

Injection process, transverse & longitudinal injection paintings, error sources, PS ripples, and also the KM impedance.

ORBIT takes indirect SC into account. The radius of the perfect conducting wall boundary for RCS, $\rho = 0.145$ m.

Space charge simulation results




The space charge force is controlled by the choice of $E_{inj.}$, rf pattern and LP

E_{inj} : 0.181 GeV

TP= 100π mm mrad

PPP: $4.2E13$ (0.5 MW)

$$\mathbf{V}_{rf} = V_1 \sin\phi + V_2 \sin\{2(\phi - \phi_s) + \phi_2\}_y$$



$\Delta v \sim -0.45$ at inj. even with rf 2h + LP.

Further increased by using rf 1h only.



Particles at $v_{xy}=6$ resonances increase.

Emittance blowup beyond aperture

and huge particle losses with rf 1h.

Well mitigated by using rf 2h + LP.

$\Delta v = -0.45$ corresponds to $1.25E14$ ppp (1.5 MW beam power) as $\Delta v \propto 1/\beta^2\gamma^3$




■ Beam instability occurs even for a beam power exceeding 0.25 MW when the ξ is fully corrected for the entire acc. cycle by **SX ac fields**.

■ No instability occurs for ξ fully corrected only at inj. by **SX dc fields**


Simulation results are well reproduced in the measurements.

Beam instability occurs at relativistic energy.
 -- Beam is stabilized by the SC at lower energy.

The growth rate is higher for $E_{inj.}$ is higher.
 --The Landau damping effect of the nonlinear SC force is smaller for higher injection energy.





Simulation



Measurement

Beam instability suppression by the SC

Dual rf + LP —
 Single rf, no LP —





Einj. = 0.181 GeV, **SX ac** ($\xi = 0$)
 PPP: 4.2E13 (0.5 MW)
 $\Delta v/v_s \gg 1$ (strong space charge)

- Beam instability occurs when the SC effect is reduced by applying dual harmonic rf voltage and also the LP.
- However, beam is stable when SC is stronger by omitting 2nd harmonic rf voltage and also the LP.
- The Landau damping effect of non-linear SC force becomes more effective to stabilize the beam.

The ORBIT code takes **indirect SC** into account, which is **important to study the beam instability with SC**.

Circular shape perfect conducting wall boundary is defined with **radius $\rho = 0.145$ m**.



- The beam tends to unstable and more destabilized as ρ is increased.
- The Landau damping effect vanishes earlier by increasing ρ and the **growth rate increases**

Beam Instability suppression at 1MW beam power

At 1 MW beam power, the SC effect, especially at lower energy should be sufficiently reduced to mitigate the beam losses.

→ Wider $\Delta p/p$ of the injected beam, apply LP and TP (100π mm mrad)

→ Choice of the betatron tunes, ξ correction,

However, reduction of the SC enhance the beam instability at higher energy.

We consider following 3 measures:

(1) Manipulation of the betatron tune (ν_x) during acceleration.

(to avoid characteristics (resonances) of the KM impedance)






(2) Further reduction of the DC ξ correction.

(to enhance the Landau damping)

(3) Smaller $\Delta p/p$ of the injected beam (should be $<0.1\%$)

(same as (2))


Suppression of Beam Instability at 1MW beam power



Even at 0.75 MW beam power:

- Beam instability w/o v_x manipulation, but
- ✓ A proper v_x manipulation stabilizes the beam.
- ✓ A narrower $\Delta p/p$ (inj. beam) gives no instability.





However, at 1 MW,
A partial ξ correction is desired.
Growth rate further increases!
Detail tune survey done.



Simulation



SX dc x 1/4

Measurement



- ⊙ Acceleration of 1 MW beam power was barely accomplished.
- ⊙ Simulation results are well reproduced in the measurements.

SX (ξ) dependence at 1 MW



In addition to a proper betatron **tune manipulation**, the ξ 1/4 or loes correction at injection and **almost no correction at extraction** were utilized to accomplish 1 MW beam power.

Summary and outlook

■ Transverse Impedance of the KM is a significant beam instability source in J-PARC RCS.

■ The ORBIT code was enhanced to cope with all time dependent Parameters for realistic beam instability studies with SC.

The beam instability suppression by the SC has been studied in detail.

■ A proper v_x manipulation and minimal ξ corrections were applied to accomplish the designed 1 MW beam power successfully.

The simulation results are well reproduced in the measurements.

● KM impedance restricts RCS flexible parameter choice for multi-user operation. R&D studies to reduce the KM impedance are in progress.


● We can achieve 1.5 MW beam power, if the KM impedance is reduced by even a half.

Acknowledgement

We acknowledge many of our colleagues for continuous support and encouragement.

M. Kinsho, N. Tani, Y. Watanabe, M. Yamamoto, K. Yamamoto, Y. Irie..

We thank Dr. J.A. Holmes of SNS for continuous support on the ORBIT code development.



RCS tune diagram and the operating point at injection.