

Status and Future Directions for High Power Neutron Production Targets

Charlotte Barbier

09/04/2019

ORNL is managed by UT-Battelle, LLC for the US Department of Energy



U.S. DEPARTMENT OF
ENERGY

What is a High-Power Neutron Source?

- Accelerators
 - kW-MW
 - High power density (MW/m^3)
 - High energy density per pulse ($\text{J}/\text{m}^3/\text{pulse}$)
- **Targets**
 - **Heavy metal (High Z: Ta, W, Hg, Pb-Bi, U)**
 - **neutron production roughly proportional to power deposited**
- Beam lines
- Detectors
- Civil construction

Key Parameters

- Proton energy E : between 1 and 5 GeV for neutron production
- Beam intensity N : nb of proton per pulse ($\sim 10^{14}$)
- Repetition rate f

- Then the power can be computed with :

$$P(MW) = 1.6 \times 10^{-16} \times E(GeV) \times N \times f(Hz)$$

High Power Neutron Sources


		Starting Operation	Target material	Power [MW]	Proton Energy [GeV]	Pulse type	Repetition [Hz]
LANSCe-Target 1		1977	Tungsten	0.1	0.8	Short	20
ISIS TS-1		1984	Tungsten	0.16	0.8	Short	40
LANSCe-Target 4		1986	Tungsten	0.1	0-0.6	Short	100
SINQ		1996	Lead	1	0.57	continuous	N/A
SNS-FTS		2006	Mercury	1.4	1.0	Short	60
ISIS TS-2		2008	Tungsten	0.032	0.8	Short	10
J-PARC		2009	Mercury	1	3.0	Short	25
CSNS-I		2018	Tungsten	0.12	1.6	Short	25
ESS		2023	Tungsten*	5	2	Long	14.7
SNS-FTS		2025	Mercury	2.0	1.3	Short	60 (45*)
SNS-STs		20??	Tungsten*	0.7	1.3	Short	15
CSNS-II		20??	Tungsten	0.5	1.6	Short	25

Main Challenges in Designing Targets

- Harsh environment
 - High radiation
 - High Temperature
- Fast deposition of energy
 - Complex dynamic → metal expands rapidly leading to strong pressure waves.
- Material properties not very well known, especially once exposed to radiation
 - Harder to predict accurately temperatures and stresses
- Gigacycle fatigues
- Fabrication
 - Weld are the weakest point

LANSCCE – Lujan Center Target (0.8 GeV, 0.1MW)


- Beam injection from above
- Tungsten target
 - MK I (1991-1998)
 - MK II (1998-2010)
 - MK III (2010-2020)
- Water cooled
- MK I target design with bare, thick tungsten cylinder suffered severe corrosion and fracture
- MK I&II experienced:
 - Highly activated water systems
 - Degradation in neutron performance
- Successive designs were segmented into plates and clad with tantalum using HIP (Hot Isostatic Pressing) process



R. Werbeck / LANL

LANSCCE – Lujan Center Target (0.8 GeV, 0.1MW)


- Beam injection from above
- Tungsten target
 - MK I (1991-1998)
 - MK II (1998-2010)
 - MK III (2010-2020)
- Water cooled
- MK I target design with bare, thick tungsten cylinder suffered severe corrosion and fracture
- MK I&II experienced:
 - Highly activated water systems
 - Degradation in neutron performance
- Successive designs were segmented into plates and clad with tantalum using HIP (Hot Isostatic Pressing) process



A.T. Nelson / LANL

LANSCe – Lujan Center Target (0.8 GeV, 0.1MW)

- Beam injection from above
- Tungsten target
 - MK I (1991-1998)
 - MK II (1998-2010)
 - MK III (2010-2020)
- Water cooled
- MK I target design with bare, thick tungsten cylinder suffered severe corrosion and fracture
- MK I&II experienced:
 - Highly activated water systems
 - Degradation in neutron performance
- Successive designs were segmented into plates and clad with tantalum using HIP (Hot Isostatic Pressing) process




A.T. Nelson / LANL

ISIS

- Two target station
 - Target Station 1 (TS1)
 - Target Station 2 (TS2)
- Operation for more than 30 years
- Highest power short-pulse spallation source prior to SNS at ORNL
 - Plate target design with water cooling
 - Uranium targets tried initially but abandoned because of short life
 - Tantalum target plates worked well but had very high activation & decay heat levels
 - Currently using tungsten with a tantalum clad
- Many features from TS1 were adapted in SNS, JSNS, CSNS...


Target Station 1

- Initial target material: uranium
 - radiation damage failures
- Reliable operations with tungsten targets
- Rely on thermocouples to detect plates failure
- Design upgrade planned for 2020
(TS1 Project):
 - 60% lighter in mass
 - neutron output improved





Target Station 1

- Initial target material: uranium
 - radiation damage failures
- Reliable operations with tungsten targets
- Rely on thermocouples to detect plates failure
- Design upgrade planned for 2020 (TS1 Project):
 - 60% lighter in mass
 - neutron output improved



ISIS Target Station 2




- Moderators very **close** to target:
 - Improved efficiency of neutrons to instrument
 - Possible because of low power
- Design oriented for **rapid** and **flexible** maintenance




ISIS-TS2 original design (Mk I) – Clad failure

Tungsten rod with tantalum cladding and vessel




No cooling at beam entrance and design assumed a flatter and larger beam profile than actual



Intergranular corrosion of tantalum cladding due to lack of cooling at beam entrance % moisture in He vessel

TS2 Target Design Evolution


- Added a water patch at the beam entrance
- Some problems at cap weld:
 - W activation products got into cooling water
 - Weld redesign
 - Clad thickness adjusted



D. Wilcox

Swiss Intense Neutron Source - SINQ Paul Scherrer Institut


- Continuous beam with injection from below
- Solid lead target rods inside SS or Zircaloy tubes
- One liquid metal target was operated
 - MEGAPIE – 1MW Pilot Experiment
- Solid lead target design evolution strove to reach MEGAPIE performance
- 11th target suffered cascade rupture of target tubes
 - Power has since been limited




MEGAPIE: Demo. of the feasibility of a liquid metal target @ 1MW

- LBE (Lead Bismuth Eutectic), $\sim 10^4 \text{ kg/m}^3$
- Got great performance: $\sim 70\%$ increase in neutron production
- High melting temperature (125 C)
 - Heating to prevent freezing in piping
 - Freezing in spill accident can be an advantage
- ^{210}Po is produced
 - Decays by α
 - Must be contained (biological hazard)
- Liquid metal corrosion is a serious issue with steels
 - Requires control of the oxygen content within a narrow range

MEGAPIE Design Details







Jet to avoid stagnation at the beam entrance




MEGAPIE Results Leveraged for Designing SINQ lead targets

- Compaction of rod bundle spacing
- D2O cooled




SINQ Target 11 (2016): Cascade of Ruptured Tubes

- Initiating event followed by succession of tube falling and blocking coolant flow
- Earlier detection of an over-focused beam
 - Operations continued after pause
- Later -
 - Water pressure increase detected
 - High activation in water detected
- Power is presently limited to < 800 kW




SNS and J-PARC: mercury Target

- Mercury is flowing into a stainless steel vessel
- A cool water shroud is used to contain potential leak




SNS Target module

Different Flow Paths




J-PARC, non-symmetric flow




SNS, symmetric flow with stagnation region at the beam entrance

Components & interfaces at the core of the SNS source




Challenges with Mercury Target



- Complex transient dynamics
- Cavitating mercury
- Addition of bubbles → hard to quantify benefits
 - Lifespan (and failure) hard to predict
- Uncertainty with the beam




Heat deposition in SS




Heat deposition in HG



SNS Target History



SNS Target History




Frequent Target Failure

- Target design has evolved to address each failure
 - T03: could not determine leak location → shroud is not removable
 - T07, T08, T11: leak at a weld at the bottom of the target → weld section has been removed.
 - T10: leak at a weld → more QA during fabrication
 - T12, T13 : nose leak due to cavitation erosion → gas injection in the target to mitigate pressure wave and cavitation erosion
 - T22: new target design → leak location and cause TBD
- It takes ~2-3 years to design a new target (from design to delivery) → benefits of improved design take some time.
- A Target Management Plan has been developed to ensure we have always enough spare and a consistent strategy in improving our target

Types and Recent History of Target Modules

Target Types

- Original flow
 - Many upgrades in newer targets
- Jet-Flow
 - Sweeping flow at beam
- Blue
 - Jet-flow + sweeping flow away from beam




Target History

- T1-T9, T11, Original flow targets
 - Three leaked at trapezoidal cover plate
- T10, First jet-flow
 - Leaked at weld away from beam
- T12-T15, Original flow targets
 - T12 and T13 had leaks from cavitation erosion outside of beam spot
 - Moved to steady power / Target Management Plan
- T16-T17, Jet-flow
- T18-T20, Jet-flow with gas injection
- T21, Original flow with gas injection
- T22, Blue design with gas injection


Benefits of Gas Injection in Mercury

- Strain decrease relative to without gas injection
[1 – ($\mu\text{L/L}$ with gas / $\mu\text{L/L}$ without gas)]

T18, 0.2 to 1.2 MW, ~0.4 slpm




T19, 1.4 MW, ~0.5 slpm




Post Irradiation Examination

Cavitation
erosion at the
end of the bulk
inlets



at one point, the
window breaks
into 2 pieces.



**Target 15
(original)**
 $P_{avg} = 1133 \text{ kW}$
 $E_{total} = 1667 \text{ MWh}$

Clear Benefits of Gas Injection

- Target 17 and 19 were both 'jet-flow' targets with similar operational histories
- The Target 19 inner wall was not fractured and had little erosion damage compared to Target 17


Target 17 – Inner Wall

Target 17
(Jet-flow Design)

No Gas Injection

$P_{avg} = 1,127 \text{ kW}$

$E_{total} = 1,936 \text{ MWh}$



Target 19 – Inner Wall


Target 19
(Jet-flow design)

Gas Injection On

$Q_{avg} = \sim 0.45 \text{ SLPM}$


$P_{avg} = 1,207 \text{ kW}$

$E_{total} = 1,987 \text{ MWh}$





CSNS

- Considered a rotating target for a while
- Final design is a fix segmented W target: 11 tungsten plate with 0.3mm tantalum cladding
- D2O cooled
- Goals:
 - Stabilizing power to 0.1 MW
 - Replacing light water to heavy water in moderators
 - Upgrade the power to 0.5 MW




Rotating Targets

- Fixed solid target at MW power are challenging:
 - Need a lot of water cooling
 - In case of a clad failure → high activation
 - Short life due to vessel radiation damage
- Rotating solid target designs offer the potential of better neutronic performance because of higher spallation target density compared to fixed targets, and longer lifetimes
- ESS (European Spallation Source)
- SNS Second Target Station (STS)




Rotating targets idea has been around for a while ...

Early Considerations for the Rotating SNQ Target




ESS: a rotating, **helium-cooled** target design


- 2 GeV, 5 MW long-pulse (2.86 ms), 14 Hz beam
- **Bare** tungsten bricks; 100°C rise/pulse



3 kg/s helium mass flow rate



$\phi \sim 2.5$ m




36 sectors of W-brick filled cassettes
Rotation speed ~ 0.4 Hz
Lifetime of 5 years at 5 MW (10 dpa to vessel)


First beam on target expected 2023

ESS: a rotating, **helium-cooled** target design


- 2 GeV, 5 MW long-pulse (2.86 ms), 14 Hz beam
- **Bare** tungsten bricks; 100°C rise/pulse



3 kg/s helium mass flow rate



$\phi \sim 2.5$ m



36 sectors of W-brick filled cassettes
Rotation speed ~ 0.4 Hz
Lifetime of 5 years at 5 MW (10 dpa to vessel)

First beam on target expected 2023

Second Target Station

- Second Target Station : rotating Target

Today




FTS

1.4 MW

Accelerator

Now

Future



FTS

2 MW


0.7 MW

Accelerator

After PPU Upgrade

STS



22 instrument slots,
8 initial instruments





After STS Upgrade

PPU Upgrade for FTS

- Accelerator is being upgraded from 1.4 MW 1 GeV to 2.8 MW 1.3 GeV
- FTS power will be limited to 2MW:
 - Increase gas injection in the target
 - Gas protection layer at the nose
- FTS hg process loop upgraded to accommodate more gas injection




STS Goal: a very bright source




- W to get better brightness
- Rotating because of high power (0.7MW)

Tungsten requires casing to prevent corrosion with water/radiation



Pulse Patterning with Independent Power Knobs

- 60 Hz is maintained, but is parsed for delivery to two targets
- STS will support independent power control to each target



SNS Today – **FTS** Only:
60 pulses at 60 Hz
spacing to FTS

2.8 MW Power **FTS/STS**:
45/60 pulses to **FTS**,
15/60 pulses to **STS**



40% more intense pulse on FTS!
Mercury Target will need to be upgraded again

Additional Thoughts

- Higher beam power is an effective approach to producing more neutrons, but has several challenges:
 - Heat removal
 - Pulse effects
 - Component (radiation) lifetimes must be manageable
- Simulations can be more and more leveraged to optimize moderators and target shape:
 - Neutronics models are closer and closer to reality
 - CFD and structural analysis much faster (HPC)
- Quick target change to make target failure less inconvenient.
- Instruments must be taken into consideration!