

MMF LINAC UPGRADE POSSIBILITIES FOR THE PULSED NEUTRON SOURCE

SK Esin, LV Kravchuk, AI Kvasha, PN Ostroumov, VL Serov
Institute for Nuclear Research, Moscow 117312, Russia

1 Introduction

Pulsed Neutron Source based on the proton accelerator is a very promising device for investigations in a fields of nuclear physics and condensed matter. Several installations have been built in USA (LANSCE, IPNS), in England (ISIS), in Japan (KENS). Pulsed Neutron Source IN-06 [1] based on the Moscow Meson Factory (MMF) Linac is under construction now. Next generation of Neutron Sources (ESS, JHF etc.) [2,3] are in R&D study.

The first stage of Neutron Source IN-06 is planned to be put into operation in 1996. The watercooled neutron target of silicious uranium will be exposed to the 500 MeV proton beam. The IN-06 design parameters (thermal neutron peak flow of $5 \cdot 10^{15} n/cm^2 \cdot s$, 35 mks pulse, 50 Hz repetition rate, average flow of $8 \cdot 10^{12} n/cm^2 \cdot s$) may be achieved after storage-compressor ring (PSR) comissioning in 1998.

We studied the possibilities of IN-06 upgrade by means of MMF Linac modernization using existing building areas, shielding and net power consumption. Our analyses have shown that peak flow of $10^{17} n/cm^2 \cdot s$ and average flow of $10^{14} n/cm^2 \cdot s$ could be achieved with the pulse length of 30 mks and repetition rate 25 Hz using PSR and neutron multiplication in target. All necessary linac innovations are not overstep the limits of the contemporary state of art. To get the above mentioned parameters we need to increase the energy of the linac up to 700 MeV and beam pulse length up to 300 mks with the repetition rate 25 Hz. Thus neutron multiplication target will be exposed to 10^{14} proton per pulse which corresponds to 10 MWt power dissipation in target [4].

2 Linac innovations

MMFLinac was designed with following parameters: maximum energy of protons and H^- ions 600 MeV; average beam current 500 mkA; pulse current 50 mA; beam pulse length 100 mks; repetition rate 100 Hz. Recently the proton energy of 423 MeV was achieved which is determined

with the number of klystrons on hand which are used for DAW Linac RF power supply. By the end of 1995 6 more klystrons will be manufactured that provide the beam energy of 500 MeV. Regular linac operation take place with the average current of 50 mkA (demonstrated 65 mkA). Total beam losses are not exceed desigh value (0, 1 ÷ 0, 2)% [5]. Beam pulse length of 70 mks and repetition rate 50 Hz are determined with experimental requirements as well as with power consumption expenditures.

The following linac systems must be upgrated to get 700 MeV proton energy and 300 mks beam pulse length:

Accelerating system. RF pulse length inrease up to 300 mks leads to the thermal heat growth in DTL as well as in DAW (disk and washer) cavities. It seems that necessary heat transfer could be provided with the water flow increase as well as with water temperature lowering in the secondary loop. Additional expenditure of electric power could be compensated due to elimination existing heaters and reduction of the water pumps number in the modernized cavity resonant frequency control system.

Energy upgrade from 600 MeV to 700 MeV could be fulfilled due to addition of one more 4-section DAW module onto the existing girder at the end of accelerating tunnel. This module has to provide the accelerating gradient of 7 MeV/m. Our experience shows that it is fully guaranted in DAW accelerating structure.

DTL Linac RF Power Supply. To meet 300 mks beam pulse we need to increase the modulator pulse length from 360 mks to 500 mks. It requires to increase the number of cells in delay line, to modify the pulsed transformer in the GMI-44A anode circuit, to increase the pulse length of the submodulator. Similar modifications have to be done in modulator of the powerful driver amplifier to increase its pulse length from 420 mks to 550 mks.

DAW Linac RF Power Supply. There are 28 991 MHz 4,75 MWt power supply channels (one for each 4-section DAW cavity) in the DAW Linac. For 300 mks 50 mA beam pulse operation we need to modify the klystron driver amplifier together with its modulator as well as the output

powerfull klystron itself. The number of cells in delay line of the driver amplifier modulator must be increased twice. The pulsed transformer must be redesigned to eliminate the iron saturation due to longer pulse.

To provide 300 mks operation with the same net power consumption and equipment sizes unchanged we have three options:

- powerfull klystron modulator is reconstructed using the same elements of the delay line. The KIU-40 old klystron maybe utilized.
- powerfull klystron modulator is modified for operation with low voltage (50 kV) high efficient 42 beam klystron "Atlant", which was developed recently by the scientific and technical firm "Thorium".
- completely new delay line has to be developed and constructed.

After some modelling and testing one of those three options has to be chosen taking into account its reliability. The RF channel for the last high accelerating gradient cavity differs from those regular ones significantly. It must be developed separately and needs additional net power.

Injection system. Existing injectors on the base of accelerating tube and 750 kV pulsed transformer have to be substituted with RFQ section designed to provide 50 mA in the pulse length of 300 mks with 25 Hz repetition rate. 198,2 MHz RFQ injector must be placed close to the first DTL cavity.

Conclusion

The fulfilment of the above mentioned steps of the MMF Linac upgrade together with proton storage-compressor ring commissioning and neutron multiplication target instead of silicious uranium one installation make the Pulsed Neutron Source based on the MMF Linac beam highly competitive.

Acknowledgment

The author are grateful to Prof. Yu. Stavissky and Dr. M. Grachev for their collaboration and helpful discussions.

References

- [1] Yu. M. Bulkin, S. F. Sidorkin, Yu. Ya. Stavisski et al. Proc. of Neutron Scattering in 90th Conf., Julich, 1985
- [2] Proc. of ICANS XI, KEK, Tsukuba, Oct. 1990, pp. 5, 32, 61, 87
- [3] Proc. of ICANS XII, RAL, Abington, UK, May 1993, P-7, P-13, P-21, P-26, T-53
- [4] M. I. Grachev, L. V. Kravchuk, Yu. Ya. Stavissky. Moscow Meson Factory Pulsed Neutron Source. Possibilities of development. Proc. of PANS-II Conference, Dubna, Russia, 1994.
- [5] S. K. Esin, L. V. Kravchuk, V. A. Matveev et al. Commissioning and operating of the Moscow Meson Factory Linac. Proc. of the LINAC Conference, Tsukuba, Japan, 1994.