Towards the Development of FPGA-Based High-Speed Data Acquisition and Online Analysis System at MHz Repetition Rate

M. Bawatna^{1,2}, A. Arnold, B. Green¹, J.-C. Deinert¹, S. Kovalev¹

¹ Helmholtz-Zentrum Dresden-Rossendorf, Bautzner Landstr. 400, 01328 Dresden, Germany ² Department of Computer Science, Technische Universität, Dresden, Germany



Motivation

In our previous work at TELBE [1,2], we developed a unique 100 kHz high repetition rate pulse-resolved arrival time monitor with high dynamic range and temporal resolution ~10 fs that overcome the major limitations of 4th generation light sources in terms of their use in time-resolved ultrafast experiments. In this work, we are demonstrating our current development for pulse-resolved detection that operates at a few MHz repetition rates with online data analysis. technology based The FPGA is new on microarchitecture and KALYPSO detector [3].

High-speed DAQ system



Current System @ TELBE



Fig 3. System block diagram of the implemented FPGAbased high speed data acquisition with online analysis at TELBE with repetition rate = 2.7 MHz, ADC 500 MSPS at 4 channels, and a few 10 fs time resolution



Fig 1. Schematic of the pulse-resolved data acquisition system developed at TELBE with repetition rate = 100 kHz, ADC at 10 MHz with 8 channels, and a few 10 fs time resolution



OUTLOOK & next steps

Fig 2. EOS of 0.9 THz undulator pulse : (a) Raw, unsorted data. Timing from delay stage position only.

(b) Added arrival time data from pulse-resolved diagnostics.(c) Averaged data in 50 fs wide bins.

- upgrade to 13 MHz repletion rate utilizing the KALYPSO detector v.3 and high throughput DAQ developments from KIT.
- Implementing 8 ADC channels at 1000 MHz and higher bit resolution.
- > Supporting two arrival-time monitor inputs in parallel.

[1] S. Kovalev et al., Probing ultra-fast processes with high dynamic range at 4th-generation light sources: Arrival time and intensity binning at unprecedented repetition rates, Struct. Dyn. 4, 024301, Pages: 1-7 (2017).
[2] B. Green et al., High-Field High-Repetition-Rate Sources for the Coherent THz Control of Matter, Sci. Rep. 6, 22256, Pages: 1-9 (2016).
[3] L. Rota et al., KALYPSO: A Mfps Linear Array Detector for Visible to NIR Radiation, Proceedings of IBIC2016, WEPG46, Pages: 740-743 (2016).

Mohamed Bawatna | High-Field THz-Driven Phenomena Group | Helmholtz-Zentrum Dresden-Rossendorf | m.bawatna@hzdr.de | www.hzdr.de